

Technical data

Rated current	10 A
---------------	------

Connection data

Solid conductor	0.08 ... 2.5 mm ² / 28 ... 14 AWG
Fine-stranded conductor	0.08 ... 2.5 mm ² / 28 ... 14 AWG
Strip length	9 ... 10 mm / 0.35 ... 0.39 inches

Physical data

Width	12 mm / 0.472 inches
Depth	74.3 mm / 2.925 inches

Mechanical data

Pluggable connector	pluggable
---------------------	-----------

Material data

Color	light gray
Fire load	0.204 MJ
Weight	11.2 g

Environmental requirements


Ambient temperature (operation)	0 ... +55 °C
Surrounding air temperature (storage)	-25 ... +85 °C
Protection type	IP20

Commercial data	
Product Group	15 (Remote I/O)
eCl@ss 10.0	27-24-26-92
eCl@ss 9.0	27-24-26-92
ETIM 8.0	EC002584
ETIM 7.0	EC002584
PU (SPU)	25 (1) Stück
Packaging type	Box
Country of origin VKOrg Germany	CN
GTIN	4050821043928
Customs tariff number VKOrg Germany	85366990990

Approvals and certificates



Approval	Standard	Certificate name
ABS American Bureau of Ship- ping	-	22-2219060
BSH Bundesamt fuer See- schiffahrt und Hydrogra- phie	-	1104
BV Bureau Veritas S.A.	-	30389/B1 BV
DNV DNV Germany GmbH	DNV-CG-0339,Aug.2021	TAA0000194
KR Korean Register of Ship- ping	-	KR HMB05880-AC001
LR Lloyds Register EMEA	-	LR22180952TA
PRS Polski Rejestr Statków	-	TE/2236/880590/19
RINA RINA Germany GmbH	-	ELE343521XG001



Approval	Standard	Certificate name
UL Underwriters Laboratories Inc.	UL 1059	E45172

Downloads

Environmental Product Compliance

Compliance Search
Environmental Product Compliance 753-110

Documentation

Manual				Bid Text			
System Manual WAGO I/O System 750 / 753	V 3.1.0 11.05.2022	pdf 8495.90 KB	↓	753-110	09.01.2019	docx 13.23 KB	↓
				753-110	19.02.2019	xml 2.99 KB	↓

CAD/CAE-Data

CAD data		CAE data	
2D/3D Models 753-110	↓	EPLAN Data Portal 753-110	↓
		WSCAD Universe 753-110	↓
		ZUKEN Portal 753-110	↓

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: www.wago.com