




## MULTI-STANDARD SC 2.1

USA: UL-listed (MTW), Canada: CSA (TEW), Europe: <HAR> H07V-K (depending on cross s.), tin-coated strands



### Benefits

- For use in the most important global markets
- Reduction in technical documentation
- Easier storage; increases the cost-effectiveness of the production process
- Works with „Conductor end sleeves XL, insulated“

### Application range

- Factory wiring
- Field wiring
- Internal wiring of devices
- Control cabinet wiring

### Product features

- Flame-retardant according IEC 60332-1-2
- Flame-retardant according to UL VW1/CSA FT1
- Oil-resistant

### Norm references / Approvals

- Multi-standard cables have conductor strands with nominal sizes in mm<sup>2</sup> or AWG/kcmil. The master size is mentioned in the table below, while the equivalent size of the other system can be found in the Appendix T16 of this catalogue. For this related secondary size the cross-section of the conductor mostly works out to be greater than the specified nominal value.
- Cable type certifications: <HAR> H07V-K acc. EN 50525-2-31, UL AWM style 1015 (by UL acc. UL standard UL 758, U.I. Lapp GmbH's UL AWM file number: E63634), (UL) MTW (by UL acc. UL standard UL 1063, U.I. Lapp GmbH's (UL) MTW file number: E198296), CSA TEW (by CSA acc. CSA standard CSA C22.2 No. 127, CSA class 5835-01)

### Product Make-up

- Fine-wire strand made of tinned-copper wires
- Special PVC-based core insulation



### Info

- The all-rounder for many markets

### Technical data

- Classification ETIM 5/6**  
 ETIM 5.0/6.0 Class-ID: EC000993  
 ETIM 5.0/6.0 Class-Description: Single core cable
- Conductor stranding**  
 Fine wire according to VDE 0295 Class 5 / IEC 60228 Class 5
- Minimum bending radius**  
 OD ≤ 8 mm: 4 x OD\* / 2 x OD\*\*;  
 8 < OD ≤ 12 mm: 5 x OD\* / 3 x OD\*\*;  
 OD > 12 mm: 6 x OD\* / 4 x OD\*\*
- Nominal voltage**  
 HAR / IEC: U0/U: 450/750 V;  
 UL (AWM): U: 600 V;  
 UL (MTW): U: 600 V;  
 CSA (TEW): U: 600 V
- Temperature range**  
 Fixed installation:  
 HAR/IEC: -40°C to +70°C;  
 UL (AWM): -40°C to +105°C;  
 UL (MTW): -40°C to +90°C;  
 CSA (TEW): up to +105°C

Conductor cross-section (mm <sup>2</sup> )	Outer diameter [mm]	m/ring	m/box	Copper index (kg/km)	Weight (kg/km)	brown	black
0.5	2.7	100		4.8	11	4160103	4160101
0.5	2.7		3000	4.8	11		4160101K
0.75	2.9	100		7.2	14	4160203	4160201
0.75	2.9		2500	7.2	14	4160203K	
1	3.1	100		9.6	16	4160303	4160301
1	3.1		2000	9.6	16	4160303K	4160301K
1.5	3.4	100		14.4	22	4160403	4160401
1.5	3.4		1500	14.4	22	4160403K	4160401K
2.5	4	100		24	37	4160503	4160501
2.5	4		900	24	37		4160501K
4	4.6	100		38.4	49	4160603	4160601
4	4.6		600	38.4	49		4160601K
6	5.1	100		57.6	67	4160703	4160701
6	5.1		400	57.6	67		4160701K
10	6.8	100		96	120	4160803	4160801
16	9	100		153.6	185	4160903	4160901
25	10.2	100		240	260	4161003	4161001
35	11.7			336	360		4161101
50	13.9			480	535		4161201
70	16			672	735		4161301
95	18.2			912	930		4161401
120	19.8			1152	1160		4161501

Conductor cross-section (mm <sup>2</sup> )	Outer diameter [mm]	m/ring	m/box	Copper index (kg/km)	Weight (kg/km)	grey	blue
0.5	2.7	100		4.8	11	4160106	4160102
0.5	2.7		3000	4.8	11	4160106K	4160102K
0.75	2.9	100		7.2	14	4160206	4160202
0.75	2.9		2500	7.2	14		4160202K
1	3.1	100		9.6	16	4160306	4160302
1	3.1		2000	9.6	16		4160302K
1.5	3.4	100		14.4	22	4160406	4160402
1.5	3.4		1500	14.4	22	4160406K	4160402K
2.5	4	100		24	37	4160506	4160502
2.5	4		900	24	37	4160506K	4160502K
4	4.6	100		38.4	49	4160606	4160602
4	4.6			38.4	49		4160602K
6	5.1	100		57.6	67	4160706	4160702
6	5.1		400	57.6	67		4160702K
10	6.8	100		96	120	4160806	4160802
16	9	100		153.6	185	4160906	4160902
25	10.2	100		240	260	4161006	4161002
35	11.7			336	360		4161102
50	13.9			480	535		4161202
70	16			672	735		4161302
95	18.2			912	930		4161402
120	19.8			1152	1160		4161502

Conductor cross-section (mm <sup>2</sup> )	Outer diameter [mm]	m/ring	m/box	Copper index (kg/km)	Weight (kg/km)	green/yellow	orange
0.5	2.7	100		4.8	11	4160100	4160109
0.5	2.7		3000	4.8	11		4160109K
0.75	2.9	100		7.2	14	4160200	4160209
0.75	2.9		2500	7.2	14		4160209K
1	3.1	100		9.6	16	4160300	4160309
1	3.1		2000	9.6	16	4160300K	4160309K
1.5	3.4	100		14.4	22	4160400	4160409
1.5	3.4		1500	14.4	22	4160400K	4160409K
2.5	4	100		24	37	4160500	4160509
2.5	4		900	24	37	4160500K	4160509K
4	4.6	100		38.4	49	4160600	4160609
4	4.6		600	38.4	49	4160600K	4160609K
6	5.1	100		57.6	67	4160700	4160709
6	5.1		400	57.6	67	4160700K	4160709K
10	6.8	100		96	120	4160800	4160809
16	9	100		153.6	185	4160900	4160909
25	10.2	100		240	260	4161000	4161009
35	11.7			336	360	4161100	
50	13.9			480	535	4161200	
70	16			672	735	4161300	
95	18.2			912	930	4161400	
120	19.8			1152	1160	4161500	

Conductor cross-section (mm <sup>2</sup> )	Outer diameter [mm]	m/ring	m/box	Copper index (kg/km)	Weight (kg/km)	dark blue	white
0.5	2.7	100		4.8	11	4160114	4160105
0.5	2.7		3000	4.8	11	4160114K	
0.75	2.9	100		7.2	14	4160214	4160205
0.75	2.9		2500	7.2	14	4160214K	
1	3.1	100		9.6	16	4160314	4160305
1	3.1		2000	9.6	16	4160314K	4160305K
1.5	3.4	100		14.4	22	4160414	4160405
1.5	3.4		1500	14.4	22	4160414K	4160405K
2.5	4	100		24	37	4160514	4160505
2.5	4		900	24	37	4160514K	4160505K
4	4.6	100		38.4	49	4160614	4160605
4	4.6		600	38.4	49	4160614K	4160605K
6	5.1	100		57.6	67	4160714	4160705
6	5.1		400	57.6	67	4160714K	
10	6.8	100		96	120	4160814	4160805
16	9	100		153.6	185	4160914	4160905

Conductor cross-section (mm <sup>2</sup> )	Outer diameter [mm]	m/ring	m/box	Copper index (kg/km)	Weight (kg/km)	green	yellow
0.5	2.7	100		4.8	11	4160111	4160110
0.75	2.9	100		7.2	14		4160210
1	3.1	100		9.6	16	4160311	4160310
1.5	3.4	100		14.4	22	4160411	4160410
2.5	4	100		24	37	4160511	4160510
4	4.6	100		38.4	49	4160611	4160610
4	4.6		600	38.4	49		4160610K
6	5.1	100		57.6	67	4160711	4160710
10	6.8	100		96	120	4160811	4160810
16	9	100		153.6	185	4160911	4160910
25	10.2	100		240	260	4161011	4161010
35	11.7			336	360	4161111	
50	13.9			480	535	4161211	

Conductor cross-section (mm <sup>2</sup> )	Outer diameter [mm]	m/ring	m/box	Copper index (kg/km)	Weight (kg/km)	violet	red
0.5	2.7	100		4.8	11	4160107	4160104
0.5	2.7		3000	4.8	11		4160104K
0.75	2.9	100		7.2	14	4160207	4160204
1	3.1	100		9.6	16	4160307	4160304
1	3.1		2000	9.6	16		4160304K
1.5	3.4	100		14.4	22	4160407	4160404
1.5	3.4		1500	14.4	22		4160404K
2.5	4	100		24	37	4160507	4160504
2.5	4		900	24	37		4160504K
4	4.6	100		38.4	49		4160604
4	4.6		600	38.4	49		4160604K
6	5.1	100		57.6	67		4160704
6	5.1		400	57.6	67		4160704K
10	6.8	100		96	120		4160804
16	9	100		153.6	185		4160904
25	10.2	100		240	260		4161004
35	11.7			336	360		4161104

Conductor cross-section (mm <sup>2</sup> )	Outer diameter [mm]	m/ring	m/box	Copper index (kg/km)	Weight (kg/km)	blue/white	pink
0.5	2.7	100		4.8	11	4160126	
0.75	2.9	100		7.2	14	4160226	
0.75	2.9		2500	7.2	14	4160226K	
1	3.1	100		9.6	16	4160326	4160308
1	3.1		2000	9.6	16	4160326K	
1.5	3.4	100		14.4	22	4160426	4160408
1.5	3.4		1500	14.4	22	4160426K	
2.5	4	100		24	37	4160526	
4	4.6	100		38.4	49	4160626	
6	5.1	100		57.6	67	4160726	
10	6.8	100		96	120	4160826	

Conductor cross-section (mm <sup>2</sup> )	Outer diameter [mm]	m/ring	m/box	Copper index (kg/km)	Weight (kg/km)	white/blue
0.5	2.7		3000	4.8	11	4160144K
0.75	2.9	100		7.2	14	4160244
0.75	2.9		2500	7.2	14	4160244K
1	3.1	100		9.6	16	4160344
1	3.1		2000	9.6	16	4160344K
1.5	3.4	100		14.4	22	4160444
2.5	4	100		24	37	4160544
2.5	4		900	24	37	4160544K
4	4.6	100		38.4	49	4160644
6	5.1	100		57.6	67	4160744
10	6.8	100		96	120	4160844

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.  
 Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Packaging size: Coil ≤ 30 kg, otherwise drum

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Non-harmonised, nominal cross-sections: 0.5 mm<sup>2</sup>, 0.75 mm<sup>2</sup>, 1 mm<sup>2</sup>, 16 mm<sup>2</sup>

\*for conventional use, \*\*for careful bending; „OD“ = outer diameter

The outer diameters stated in the part number table are maximum values.

**Similar products**

- H07V-K <HAR> refer to page 213
- MULTI-STANDARD SC 2.2 refer to page 221

**Accessories**

- DIN-assorted boxes conductor end sleeves refer to page 995
- Conductor end sleeves XL, insulated refer to page 996
- PEW 8.87 crimping pliers refer to page 1000