



## UNITRONIC® BUS CC

CC-Link bus cable for fixed installation - UL-verified

**Info**

- Lapp Kabel is a regular member of the user organisation CC-Link Partner Association (CLPA), Japan.

**Benefits**

- The CC-Link® system was developed by Mitsubishi Electric Automation, Japan.
- This CC-Link® bus cable has successfully passed the CC-Link® Conformance Test in Japan.

**Application range**

- CC-Link® (Control & Communication Link) = field bus network, for both control as well as information data to provide efficient, integrated factory and process automation.
- Fixed installation of the CC-Link® network



**Product features**

- Transmission rate in relation to the distance
- 156 kbit/s 1.200 m
- 625 kbit/s 600 m
- 2,5 Mbit/s 200 m
- 5,0 Mbit/s 110-150 m
- 10 Mbit/s 50-100 m
- Flame-retardant according to CSA FT4 UL Vertical-Tray Flame Test
- SUN RES acc. to UL 1581

**Norm references / Approvals**

- CM UL/CSA certification 75°C or PLTC Sun Res

**Product Make-up**

- Bare stranded copper wires
- Core insulation: PE
- Overall screening of braided tinned-copper strands
- Outer sheath: PVC, red (RAL 3000)

**Technical data**

- Classification ETIM 5/6**  
ETIM 5.0/6.0 Class-ID: EC000830  
ETIM 5.0/6.0 Class-Description: Data cable
- Peak operating voltage**  
300 V
- Conductor resistance**  
11 Ω/1,000 ft. (305 m) at 20°C
- Minimum bending radius**  
Fixed installation: 5 x outer diameter  
Flexing: 8 x outer diameter
- Test voltage**  
2000 V
- Characteristic impedance**  
110 Ω at 1 MHz
- Temperature range**  
-40°C to +70°C

Article number	Article designation	Number of cores and AWG size	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
<b>UNITRONIC® BUS CC</b>					
2170360	UNITRONIC® BUS CC	3 x 1 x AWG20	7.7	38.8	76.6

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.  
Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.  
Please find our standard lengths at: [www.lappkabel.de/en/cable-standardlengths](http://www.lappkabel.de/en/cable-standardlengths) / CC-Link® is a registered trademark of CC-Link Partner Association, Japan (CLPA)  
Photographs and graphics are not to scale and do not represent detailed images of the respective products.



## UNITRONIC® BUS CC FD P FRNC

CC-Link bus cable for high fleible applications - UL-verified

**Info**

- Lapp Kabel is a regular member of the user organisation CC-Link Partner Association (CLPA), Japan.

**Benefits**

- The CC-Link® system was developed by Mitsubishi Electric Automation, Japan.

**Application range**

- CC-Link® (Control & Communication Link) = field bus network, for both control as well as information data to provide efficient, integrated factory and process automation.
- For highly flexible applications (power chains, moving machine parts)



**Product features**

- Transmission rate in relation to the distance
- 156 kbit/s 1.200 m
- 625 kbit/s 600 m
- 2,5 Mbit/s 200 m
- 5,0 Mbit/s 110-150 m
- 10 Mbit/s 50-100 m
- Halogen-free
- Flame-retardant according IEC 60332-1-2

**Norm references / Approvals**

- AWM 20233 80 °C 300V

**Product Make-up**

- Bare stranded copper wires
- Core insulation: PE
- Inner sheath: FRNC
- Overall screening of braided tinned-copper strands
- Outer sheath: PUR, red (RAL 3000)

**Technical data**

- Classification ETIM 5/6**  
ETIM 5.0/6.0 Class-ID: EC000830  
ETIM 5.0/6.0 Class-Description: Data cable
- Certifications**  
UL AWM Style 20233
- Peak operating voltage**  
300 V
- Conductor resistance**  
11 Ω/1,000 ft. (305 m) at 20°C
- Minimum bending radius**  
Fixed installation: 4 x outer diameter  
Moved: 10 x outer diameter
- Test voltage**  
2000 V
- Characteristic impedance**  
110 Ω at 1 MHz
- Temperature range**  
-40°C to +80°C

Article number	Article designation	Number of cores and AWG size	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
<b>UNITRONIC® BUS CC FD P FRNC</b>					
2170370	UNITRONIC® BUS CC FD P FRNC	3 x 1 x AWG20	8.5	39.9	84

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.  
Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.  
Please find our standard lengths at: [www.lappkabel.de/en/cable-standardlengths](http://www.lappkabel.de/en/cable-standardlengths) / CC-Link® is a registered trademark of CC-Link Partner Association, Japan (CLPA)  
Photographs and graphics are not to scale and do not represent detailed images of the respective products.