



ÖLFLEX® CLASSIC 110 CY BLACK 0,6/1 kV



Info

- Good outdoor performance
- EMC/Screened

Application range

- Plant engineering
Industrial machinery
Heating and air-conditioning systems
Power stations
- For frequency converter-powered 3-phase AC motors
- In EMC-sensitive environments (electromagnetic compatibility)
- Servo Drive Connection Cable
- For fixed installation as well as occasional flexing at free, non-continuously recurring movement without tensile load
- Each dimension with nominal/ minimum average wall thickness of the outer sheath of at least 1.8 mm: For applications where a strengthened outer sheath may turn out to be advantageous

Product features

- Flame-retardant according IEC 60332-1-2
- UV and weather-resistant according to ISO 4892-2
- Ozone-resistant according to EN 50396
- High degree of screening
low transfer impedance
(max. 250 Ω/km at 30 MHz)

Norm references / Approvals

- Based on VDE 0250-1 and HD 627-1 S1

Product Make-up

- Fine-wire strand made of bare copper wires
- PVC insulation LAPP P8/1
- PVC inner sheath, black
- Tinned-copper braiding
- PVC outer sheath, black (RAL 9005)

Technical data

- Classification ETIM 5/6**
ETIM 5.0/6.0 Class-ID: EC000104
ETIM 5.0/6.0 Class-Description:
Control cable
- Core identification code**
Black with white numbers acc. to VDE 0293-1
- Conductor stranding**
Fine wire according to VDE 0295, class 5/IEC 60228 class 5
- Minimum bending radius**
Static/Occ. moved: 6/20xOD*
- Nominal voltage**
U0/U: 600/1000 V
- Test voltage**
4000 V
- Protective conductor**
G = with GN-YE protective conductor
X = without protective conductor
- Temperature range**
Occasional flexing: -5 °C to +70 °C
Fixed installation: -40 °C to +80 °C

Article number	Number of cores and mm ² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CLASSIC 110 CY BLACK				
1121232	2 X0,75	10.5	46	183
1121233	3 G0,75	10.9	56	210
1121235	4 G0,75	11.4	67	214
1121236	4 X0,75	11.4	67	214
1121237	5 G0,75	12.1	78	272
1121241	7 G0,75	12.9	97	242
1121247	12 G0,75	15.8	168	464
1121251	18 G0,75	18.0	229	616
1121254	25 G0,75	20.7	296	762
1121266	2 X1,0	10.8	52	198
1121267	3 G1,0	11.2	66	228
1121268	3 X1,0	11.2	66	228
1121269	4 G1,0	11.8	79	261
1121270	4 X1,0	11.8	79	261
1121271	5 G1,0	12.6	93	300
1121274	7 G1,0	13.3	117	335
1121280	12 G1,0	16.4	204	522
1121284	18 G1,0	18.7	280	687
1121290	25 G1,0	21.6	369	884
1121306	2 X1,5	11.8	69	243
1121307	3 G1,5	12.3	87	214
1121308	3 X1,5	12.3	87	273
1121309	4 G1,5	13.0	102	290
1121310	4 X1,5	13.0	102	290

Article number	Number of cores and mm ² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
1121311	5 G1,5	13.9	125	352
1121314	7 G1,5	15.0	180	448
1121320	12 G1,5	18.7	281	690
1121324	18 G1,5	21.8	391	938
1121328	25 G1,5	25.1	518	1180
1121340	3 G2,5	13.5	123	315
1121342	4 G2,5	14.6	168	349
1121344	5 G2,5	15.7	204	515
1121346	7 G2,5	17.0		619
1121349	12 G2,5	21.7	421	936
1121360	4 G4	16.2	238	587
1121361	5 G4	17.7	302	689
1121362	7 G4	19.0	396	828
1121367	4 G6	17.7	318	715
1121368	5 G6	19.2	419	862
1121372	4 G10	21.7	574	875
1121373	5 G10	23.0	612	1037
1121377	4 G16	24.3	809	1656
1121378	5 G16	26.7	935	1500
1121381	4 G25	29.8	1165	2179
1121385	4 G35	32.7	1683	2893
1121388	4 G50	39.6	2368	4094
1121391	4 G70	44.5	3261	5467
1121394	4 G95	51.0	4055	5849
1121397	4 G120	58.1	5225	7509

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

*OD = Outer diameter

Similar products

- ÖLFLEX® CLASSIC 135 CH BK 0,6/1 kV refer to page 67

Accessories

- SKINTOP® BRUSH ADD-ON refer to page 700
- SKINTOP® MS-HF-M BRUSH refer to page 708
- SKINTOP® MS-M BRUSH refer to page 702