

## Connector RJ45 CAT.5e Hirose TM 11



### Product features

- Suitable for cross section (AWG24-27)
- Connection type: crimp
- Core insulation: app. 0,9-1,0 mm
- Max. outer sheath diameter: 5.8 mm
- Anti-kink protection: beige
- Set includes: RJ plug, anti-kink protection and guide plate
- Screened version

### Technical data

**Classification ETIM 5/6**  
 ETIM 5.0/6.0 Class-ID: EC002641  
 ETIM 5.0/6.0 Class-Description:  
 Modular connector (industrial connector)

Article number	Article designation
<b>Connector RJ45 CAT.5e Hirose TM 11</b>	
CE6321	Connector RJ45 CAT.5e Hirose TM 11

Hirose is a registered trademark of the HIROSE ELECTRIC Group  
 Other colours are available upon request.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

### Accessories

- Crimping tool RJ45 Hirose refer to page 473

## Connector RJ45 CAT.5 Stewart SS37



### Product features

- Screened version
- Suitable for stranded conductors (AWG26)
- Included: bend protection and guide plate
- Anti-kink protection: light grey
- Max. outer sheath diameter: 5.72 mm

### Technical data

**Classification ETIM 5/6**  
 ETIM 5.0/6.0 Class-ID: EC002641  
 ETIM 5.0/6.0 Class-Description:  
 Modular connector (industrial connector)

Article number	Article designation
<b>Connector RJ45 CAT.5 Stewart SS37</b>	
CE6323	Connector RJ45 CAT.5 Stewart SS37

Stewart is a registered trademark of Bel Fuse Inc.

Other colours are available upon request.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

### Accessories

- Crimping tool RJ45 Stewart refer to page 474

## Field-Terminable Connector RJ45 CAT.5e FM45



### Product features

- Screened version
- Suitable for AWG 23 - 26, AWG 22 possible with restrictions
- IDC/piercing terminal according to 60352-4
- Suitable for solid and stranded conductors
- Suitable for use in industrial applications

### Technical data

**Classification ETIM 5/6**  
 ETIM 5.0/6.0 Class-ID: EC002641  
 ETIM 5.0/6.0 Class-Description:  
 Modular connector (industrial connector)

**IP** Protection rating  
 IP 20

**Ambient temperature (operation)**  
 -20°C to +70°C

Article number	Article designation
<b>RJ45 connector acc. to T568A</b>	
21700540	Field-Terminable Connector RJ45 CAT.5e FM45

Photographs and graphics are not to scale and do not represent detailed images of the respective products.