



EPIC® MH 4

High flexibility by the use of any combination of inserts in one connector



Info

- Modular connector system, pluggable with the market standard
- Power module 4 pole for compact power transmission

Suitable housing

- EPIC MH 6 R Page 570
- EPIC MH 10 R Page 570
- EPIC MH 16 R Page 570
- EPIC MH 24 R Page 570
- EPIC® H-B housing use in high version

Suitable contacts:

- EPIC MH 4.0mm Contacts Page 595

Benefits

- Power module 4 pole for compact power transmission
- Crimp connection for permanent vibration proof contact
- EPIC® MH system is mateable with the market standard
- The mix of different functions in one plug guarantees high flexibility
- Railway applications
 - Fire protection on railway vehicles: Test according EN 45545-2. Requirement sets R22 and R23. Hazard level HL1, HL2 and HL4

Application range

- Mechanical engineering
- Robotics industry
- Plant engineering
- Renewable energy
- Railway applications / vehicle construction

Technical data

<p>Classification ETIM 5/6 ETIM 5.0/6.0 Class-ID: EC002641 ETIM 5.0/6.0 Class-Description: Modular connector (industrial connector)</p> <p>Rated voltage (V) 830 V</p> <p>Rated impulse voltage 8 kV</p> <p>Rated current (A) 40</p> <p>Pollution degree 3</p> <p>Flammability UL94 V-0</p>	<p>Contact resistance < 5 mOhm</p> <p>Number of contacts 4</p> <p>Termination methods Crimp termination: 1.5 mm² - 10 mm²</p> <p>Material Polyamide, glass fibre-reinforced</p> <p>Cycle of mechanical operation 500</p> <p>Certifications UL-tested: UL File Number: E75770</p> <p>Temperature range -40 °C +125 °C</p>
---	--

Article number	Article description	Contact type	Number of operating contacts	Slots	Pieces / PU
EPIC® MH 4					
44423216	EPIC® MHS 4 CM	male	4	1	10
44423217	EPIC® MHB 4 CM	female	4	1	10

Photographs and graphics are not to scale and do not represent detailed images of the respective products.