

Rectangular connectors • EPIC® MH modular system module



EPIC® MH Gigabit Modul

The mixed assembly guarantees high flexibility. For applications in mechanical and plant engineering, for printing machines and slide-in technology.



- Modular connector system, mateable with the market standard
- Gigabit module for Ethernet data rates up to 10 GBit/s, Cat. 7





Suitable housing

- EPIC MH 6 R Page 570
- EPIC MH 10 R Page 570
- EPIC MH 16 R Page 570
- EPIC MH 24 R Page 570

Suitable contacts:

• EPIC® MH 1.0mm contacts machined Page 585

Benefits

- Gigabitmodule, all around shielded, 4 pair of wires, for Ethernet data rates up to 10 GBit/s, Cat. 7
- EPIC® MH system is mateable with the market standard
- The mix of different functions in one plug guarantees high flexibility
- Railway applications
- Fire protection on railway vehicles: Test according EN 45545-2. Requirement sets R22 and R23. Hazard level HL1, HL2 and HL4

Application range

- · Industrial machinery and plant engineering
- Industry 4.0 applications
- Robotics industry
- Renewable energy
- Railway applications / vehicle construction

Technical data



Rated voltage (V)

50

Rated impulse voltage 0.8 kV

Rated current (A)

Amp.

Flammability
UL94 V-0



Number of contacts

A

Material PA Polyamid Zinc die-cast

Cycle of mechanical operation 500

Temperature range -40°C

+125°C

Article number	Article description	Contact type	Connection cross section (mm²)	Slots	Pieces / PU
EPIC® MH Gigabit	Kit				
44423291	EPIC® MHS Gigabit Kit small	male	5.00 - 7.00	1	1
44423292	EPIC® MHB Gigabit Kit small	female	5.00 - 7.00	1	1
44423326	EPIC® MHS Gigabit Kit medium	male	7.00 - 10.00	1	1
44423327	EPIC® MHB Gigabit Kit medium	female	7.00 - 10.00	1	1
EPIC® MH Gigabit	Insulating body				
44423276	EPIC® MHS Gigabit	male		1	10
44423277	EPIC® MHB Gigabit	female		1	10
EPIC® MH Gigabit	contact body metal				
44423278	EPIC® MHS Gigabit PIN	male			10
44423279	EPIC® MHS Gigabit PIN + GND	male			10
44423280	EPIC® MHB Gigabit PIN	female			10
44423281	EPIC® MHB Gigabit PIN + GND	female			10
EPIC® MH Gigabit	cable clamp				
44423282	EPIC® MH Clamp 5 - 7 mm		5.00 - 7.00		10
44423283	EPIC® MH Clamp 7 - 10 mm		7.00 - 10.00		10
44423284	EPIC® MH Clamp 10 - 12 mm		10.00 - 12.00		10

Photographs and graphics are not to scale and do not represent detailed images of the respective products.