



**EPIC® ULTRA H-B 24 TS QB**

The robust and reliable industry connector housing as EMC version



**Info**

- EMC protection
- Corrosion-resistant
- SKINTOP® integrated cable gland

**EPIC® ULTRA H-B 24 AG QB**

The robust and reliable industry connector housing as EMC version



**Info**

- EMC protection
- Corrosion-resistant

**Benefits**

- Optimum, low-resistance 360° screening
- All-purpose due to high corrosion resistance and high environmental protection.
- Space-saving due to compact dimensions
- Faster than any other comparable system
- High mechanical resistance

**Application range**

- In EMC-sensitive environments
- For fixed and flexible applications (e.g. machinery building, wind turbines)
- Construction machinery
- Electric motor manufacturing

**Product features**

- Housings with the BRUSH addition come with BRUSH cable screen contacting
- Pluggable with standard housings
- Corrosion-resistant according to DIN EN 6988
- Resistance to cyclic salt spray is tested according to IEC 68-2-52, severity level 2
- Salt spray testing according to DIN EN ISO 9227, method NSS, period of test 480 hours

**Suitable inserts**

- Refer to Selection Table A 10 to select the required inserts and housings

**Technical data**

<p><b>Classification ETIM 5/6</b>                  ETIM 5.0/6.0 Class-ID: EC000437                  ETIM 5.0/6.0 Class-Description:                  Housing for industrial connectors</p>	<p><b>Protection rating</b>                  IP 65                  NEMA 250, UL50E: 12 (latched)</p> <p><b>Temperature range</b>                  -40°C to +100°C</p>
<p><b>Material</b>                  Housing: nickel-plated zinc die-casting                  Lever and bolts: stainless steel                  Sealing: NBR                  Cable gland                  Body: nickel-plated brass                  Insert: PA                  Seal: special elastomer</p>	

Article number	Article description	Clamping range in mm	Minimum Ø above braiding (mm)	Pieces / PU
<b>H-B housing: hood (side cable entry, bolts for double lever)</b>				
70250219	ULTRA H-B 24 TS QB 7-15	7 - 15		1
70250263	ULTRA H-B 24 TS QB 7-15 BRUSH	7 - 15	8	1
70250220	ULTRA H-B 24 TS QB 11-21	11 - 21		1
70250221	ULTRA H-B 24 TS QB 11-21 BRUSH	11 - 21	8	1
<b>H-B housing: panel-mount base (double lever)</b>				
70250222	ULTRA H-B 24 AG QB			1

Photographs and graphics are not to scale and do not represent detailed images of the respective products.