




SKINTOP® GRIP-M

Info

- Brass cable gland with with centred strain relief and kink protection



Benefits

- Protection against kinking and rip out of cables
- High strain relief
- For high mechanical stress
- Reliable bending and anti-kink protection

Application range

- Saddle clamp strain relief gland for harsh application conditions.
- Portable equipment
- Machines and systems on building sites
- Crane and conveying machinery
- Charging infrastructure for EV's

Norm references / Approvals

- Metric connection thread acc. to DIN EN 60423
- Basis for technical information DIN IEC 62444
- Tested according to IEC 62196-1: Conductive charging of electric vehicles

Technical data

- Classification ETIM 5/6**
ETIM 5.0/6.0 Class-ID: EC000441
ETIM 5.0/6.0 Class-Description: Cable screw gland
- Caution**
Refer to the instruction leaflet for the installation dimensions and torques
- Material**
Body: Nickel-plated brass
Sealing: CR/NBR
O-Ring - NBR
- Protection rating**
IP 68 - 10 bar
IP 69
- Temperature range**
-40°C to +100°C

Article number	Article designation / size	Clamping range ØF (mm)	SW wrench size mm	Overall length, C (mm)	Thread length, D (mm)	Pieces / PU
SKINTOP® GRIP-M						
53113180	M 16 x 1,5	4,5-10	20	41.0	7	25
53113200	M 20 x 1,5	7-13	24	46.0	8.5	25
53113210	M 25 x 1,5	9-17	29	48.5	8	25
53113220	M 32 x 1,5	11-21	36	56.5	9	25

Photographs and graphics are not to scale and do not represent detailed images of the respective products.