




SKINDICHT® SHV-M FKM



**Benefits**

- For high temperatures
- Resistant to oils, solvents, acids and chemicals
- Watertight
- High strain relief
- Robust

**Application range**

- Watertight and high temperature-resistant cable gland with special conical FKM sealing element
- Brickworks
- Sewage treatment plants
- Car wash sites

**Product Make-up**

- 1 fitting
- 2 washers
- 3 FKM sealing cone
- 4 brass cones
- 5 compression screws

**Note**

- Counter nut to be used: SKINDICHT® SM-M
- Example description: SHV-M-FKM 20/11/7  
20 = metric connection thread  
11 = PG function thread  
7 = clear opening of sealing cone

**Technical data**

**Classification ETIM 5/6**  
ETIM 5.0/6.0 Class-ID: EC000441  
ETIM 5.0/6.0 Class-Description: Cable screw gland

**Caution**  
The installation dimensions can be found in appendix T21

**Material**  
Body: nickel-plated brass  
Sealing cone: FKM  
O-ring: FKM

**Protection rating**  
IP 68 - 10 bar

**Temperature range**  
-15°C to +200°C

Article number	Article designation / size	Clamping range ØF (mm)	Function thread PG	SW wrench size mm	Overall length, C (mm)	Thread length, D (mm)	Clear opening F (mm)	Pieces / PU
<b>SKINDICHT® SHV-M FKM</b>								
52105430	M 12 x 1,5	3,8 - 4,8	7	14.0 / 14.0	26.0	5	5	50
52105440	M 16 x 1,5	4,8 - 5,8	9	18.0 / 17.0	27.5	5	6	50
52105450	M 16 x 1,5	5,8 - 6,8	9	18.0 / 17.0	27.5	5	7	50
52105460	M 20 x 1,5	5,8 - 6,8	11	22.0 / 20.0	31.0	6	7	25
52105470	M 20 x 1,5	6,8 - 8,8	11	22.0 / 20.0	31.0	6	9	25
52105480	M 20 x 1,5	8,5 - 10,8	13.5	22.0 / 22.0	32.5	6	11	25
52105490	M 20 x 1,5	6,8 - 8,8	13.5	22.0 / 22.0	32.5	6	9	25
52105500	M 20 x 1,5	10,8 - 12,8	16	24.0 / 24.0	34.5	6	13	25
52105510	M 20 x 1,5	13,8 - 14,8	16	24.0 / 24.0	34.5	6	15	25
52105520	M 25 x 1,5	15,8 - 17,8	21	30.0 / 30.0	38.0	7	18	25
52105530	M 25 x 1,5	17,5 - 19,8	21	30.0 / 30.0	38.0	7	20	25
52105540	M 32 x 1,5	19,5 - 21,8	29	40.0 / 40.0	44.5	8	22	10

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

**Accessories**

- SKINDICHT® SM-M refer to page 744

