



SKINDICHT® BLK-M / SKINDICHT® BLK-GL-M



Benefits

SKINDICHT® BLK-M

- For closing pre-threaded holes
- Cost-effective solution

SKINDICHT® BLK-GL-M

- For closing pre-threaded holes
- High stability due to glass fibre reinforcement

Application range

- Control cabinet manufacturing
- Distribution box
- Junction boxes

Product Make-up

- Metric connection thread acc. to DIN EN 60423
- Basis for technical information DIN IEC 62444

Technical data



Classification ETIM 5/6

ETIM 5.0/6.0 Class-ID: EC000032
ETIM 5.0/6.0 Class-Description: Plug for cable screw gland



Colour delivered

SKINDICHT® BLK-M
Light grey (RAL 7035)
SKINDICHT® BLK-GL-M
Silver grey (RAL 7001)
Light grey (RAL 7035)
Black (RAL 9005)



Material

SKINDICHT® BLK-M
Fire behaviour according to UL 94 HB
Impact-resistant polystyrene
SKINDICHT® BLK-GL-M
Fire behaviour according to UL 94 HB
Polyamide, glass fibre-reinforced



Protection rating

IP 54
IP 68 (with O-Ring)



Temperature range

SKINDICHT® BLK-M
-25 °C to +60 °C
SKINDICHT® BLK-GL-M
-40 °C to +100 °C

Article number	Article designation / size	Thread length, D (mm)	Pieces / PU
SKINDICHT® BLK-M			
52006600	M 12 x 1,5	6	100
52006610	M 16 x 1,5	6	100
52006620	M 20 x 1,5	6	100
52006630	M 25 x 1,5	8	100
52006640	M 32 x 1,5	8	50
52006650	M 40 x 1,5	8	25
52006660	M 50 x 1,5	10	25
52006670	M 63 x 1,5	12	25
SKINDICHT® BLK-GL-M silver-grey			
52006101	M 12 x 1,5	6	100
52006111	M 16 x 1,5	6	100
52006121	M 20 x 1,5	6	100
52006131	M 25 x 1,5	8	100
52006141	M 32 x 1,5	8	50
52006151	M 40 x 1,5	8	25
52006161	M 50 x 1,5	10	25
52006171	M 63 x 1,5	12	25
SKINDICHT® BLK-GL-M light grey			
52006100	M 12 x 1,5	6	100
52006110	M 16 x 1,5	6	100
52006120	M 20 x 1,5	6	100
52006130	M 25 x 1,5	8	100
52006140	M 32 x 1,5	8	50
52006150	M 40 x 1,5	8	25
52006160	M 50 x 1,5	10	25
52006170	M 63 x 1,5	12	25
SKINDICHT® BLK-GL-M black			
52006103	M 12 x 1,5	6	100
52006113	M 16 x 1,5	6	100
52006123	M 20 x 1,5	6	100
52006133	M 25 x 1,5	8	100