

## SKINDICHT® SM / SKINDICHT® SM-PE



## SKINDICHT® SM

## Benefits

## SKINDICHT® SM-PE

- Cutting edges cut through the insulating layer, thus guaranteeing an optimum EMC contact

## Application range

## SKINDICHT® SM

- Used when a gland has to be countered, or in through-holes on thin-walled housings

## SKINDICHT® SM-PE

## SKINDICHT® SM-PE

- For lacquered, anodised or powder-coated housings.

## Product Make-up

- PG connection thread

## Technical data

**Classification ETIM 5/6**  
ETIM 5.0/6.0 Class-ID: EC000940  
ETIM 5.0/6.0 Class-Description:  
Locknut for cable screw gland

**Material**  
Nickel-plated brass

**Temperature range**  
-60°C to +200°C

Article number	Article designation / size	Height (mm)	SW wrench size mm	Far corner dimension	Pieces / PU
<b>SKINDICHT® SM</b>					
52003490	PG 7	2.8	15	16.6	100
52003500	PG 9	2.8	18	20	100
52003510	PG 11	3.0	21	23.5	100
52003520	PG 13,5	3.0	23	25.5	100
52003530	PG 16	3.0	26	29	100
52003540	PG 21	3.5	32	35.5	50
52003550	PG 29	3.5	41	45	50
52003560	PG 36	5.0	51	56	25
52003570	SM 42	5.0	60	65	25
52003580	PG 48	5.5	64	69	25
<b>SKINDICHT® SM-PE</b>					
52103200	PG 7	4.7	15	17.3	100
52103210	PG 9	4.7	18	20.8	100
52103220	PG 11	4.7	21	24.3	100
52103230	PG 13,5	4.7	23	26.6	100
52103240	PG 16	4.7	26	30	100
52103250	PG 21	5.2	32	37	50
52103260	PG 29	5.7	41	47.3	50
52103270	PG 36	6.5	51	58.9	50

Photographs and graphics are not to scale and do not represent detailed images of the respective products.



## SKINDICHT® SM INOX



## Application range

- Used when a gland has to be countered, or in through-holes on thin-walled housings

## Product Make-up

- PG connection thread

## Technical data

**Classification ETIM 5/6**  
ETIM 5.0/6.0 Class-ID: EC000940  
ETIM 5.0/6.0 Class-Description:  
Locknut for cable screw gland

**Material**  
Stainless steel

**Temperature range**  
-60°C to +200°C

Article number	Article designation / size	Height (mm)	SW wrench size mm	Pieces / PU
<b>SKINDICHT® SM INOX</b>				
52032517	PG 7	3.5	17	50
52032553	PG 9	3,5	19	50
52032559	PG 11	3,5	22	50
5203254	PG 13,5	4.0	24	50
52032555	PG 16	4.0	27	50
52032556	PG 21	4,5	32	25
52032557	PG 29	5,5	41	10
52032558	PG 36	6.0	51	10

Photographs and graphics are not to scale and do not represent detailed images of the respective products.