

Liquid-tight conduits (metal + jacket) • Metal conduit with thick-walled jacket



SILVYN® COMPACT M



Info

- Space-saving due to compact dimensions

Benefits

- Space-saving application
- For high mechanical stress
- High tensile strength
- Corrosion-resistant

Application range

- In combination with protective conduit:
- Suitable for SILVYN® HTDL/EF/OR/HCX/HFX
- Mechanical engineering
- Railway applications

Product Make-up

- Metric connection thread
- Hexagonal collar
- Threaded sleeve
- Cap nut

Suitable conduits

- SILVYN® HTDL Page 907
- SILVYN® EF Page 908
- SILVYN® OR Page 908
- SILVYN® HCX Page 909
- SILVYN® HFX Page 909

Technical data

Classification ETIM 5/6
 ETIM 5.0/6.0 Class-ID: EC001180
 ETIM 5.0/6.0 Class-Description: Screw connection for protective metallic hose

Norm references / Approvals
 UL 514B

On request
 Available in stainless steel

Material
 Body: nickel-plated brass
 Sealing: polyamide
 O-ring: NBR

Protection rating
 IP 66
 IP 67

Temperature range
 -45°C to +105°C

Article number	Metric size	Suitable for SILVYN® HTDL/EF/OR/HCX/HFX	Pieces / PU
SILVYN® COMPACT M			
61803846	16 x 1.5	5/16"	10
61803800	16 x 1.5	3/8"	10
61803847	20 x 1.5	5/16"	10
61803801	20 x 1.5	3/8"	10
61803802	20 x 1.5	1/2"	10
61803803	25 x 1.5	3/4"	5
61803804	32 x 1.5	1"	5
61803805	40 x 1.5	1 1/4"	5
61803806	50 x 1.5	1 1/2"	2
61803807	63 x 1.5	2"	2
SILVYN® COMPACT 45° M			
61803848	16 x 1.5	5/16"	10
61803850	16 x 1.5	3/8"	10
61803849	20 x 1.5	5/16"	10
61803851	20 x 1.5	3/8"	10
61803852	20 x 1.5	1/2"	10
61803853	25 x 1.5	3/4"	5
61803854	32 x 1.5	1"	5
SILVYN® COMPACT 90° M			
61803808	16 x 1.5	3/8"	10
61803809	20 x 1.5	3/8"	10
61803810	20 x 1.5	1/2"	10
61803811	25 x 1.5	3/4"	5
61803812	32 x 1.5	1"	5
61803813	40 x 1.5	1 1/4"	5
61803814	50 x 1.5	1 1/2"	2
61803815	63 x 1.5	2"	2

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Accessories

- SKINDICHT® SM-M refer to page 744