



SILVYN® LTP



Benefits

- Protects against liquids
- High-tensile
- Robust
- High crush-resistance
- Largely resistant to oil and acids, UV-resistant

Application range

- Mechanical engineering
- Outdoors
- Transformer construction
- Railway applications
- Paper industry

Product Make-up

- Spirally-wound heavy metal protective conduit with roughened profile
- Plastic outer sheath

Technical data

Classification ETIM 5/6
 ETIM 5.0/6.0 Class-ID: EC001179
 ETIM 5.0/6.0 Class-Description: Protective metallic hose

Certifications
 IEC EN 61386-23

Colour delivered
 Black (RAL 9005), UV-resistant

Material
 Steel, galvanised
 PVC sheath

Temperature range
 -20°C to +105°C

Article number	Nominal size	ID x OD mm	Bending radius (mm)	PU ring (m)
SILVYN® LTP				
61805400	10 - 1/4"	7.0 x 11.8	35	50
61805410	12 - 5/16"	10.0 x 14.2	40	50
61805420	16 - 3/8"	12.6 x 17.8	45	50
61805430	20 - 1/2"	16.0 x 21.1	65	50
61805440	25 - 3/4"	21.0 x 26.4	100	25
61805450	32 - 1"	26.5 x 33.1	135	25
61805460	40 - 1 1/4"	35.4 x 41.8	175	10
61805470	50 - 1 1/2"	40.4 x 47.9	230	10
61805480	63 - 2"	51.6 x 59.7	280	10

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Similar products

- SILVYN® OR refer to page 908

Accessories

- SILVYN® LTPG-M refer to page 914
- SILVYN® LTPS-M refer to page 914
- SILVYN® LTP 45° M refer to page 914
- SILVYN® LTP 90° M refer to page 914