

Insulated screwdrivers according to IEC 60900:2005, classification VDE 0682, part 201. Individually tested in a water bath with a testing voltage of 10,000 V.

Electrician screwdriver

according to DIN EN 60900; VDE 0682 - 201:2005 - 01; DIN ISO 2380

2.5 x 0.4	75	160	12	11 7701
3.0 x 0.5	100	185	12	11 7702
3.5 x 0.6	100	185	12	11 7703
4.0 x 0.8	100	185	12	11 7704
5.5 x 1.0	125	220	12	11 7705
6.5 x 1.2	150	245	12	11 7706
8.0 x 1.2	175	285	12	11 7708
10.0 x 1.6	200	310	12	11 7710



Phillips cross-head screwdriver

according to DIN EN 60900; VDE 0682 - 201:2005 - 01; DIN ISO 8764

PH 0	60	145	12	11 7730
PH 1	80	165	12	11 7731
PH 2	100	195	12	11 7732
PH 3	150	260	12	11 7733

Pozidriv crosshead screwdriver

according to DIN EN 60900; VDE 0682 - 201:2005 - 01; DIN ISO 8764

PZ 0	60	145	12	11 7740
PZ 1	80	165	12	11 7741
PZ 2	100	195	12	11 7742
PZ 3	150	260	12	11 7743

Special screwdrivers with combination profile

according to DIN EN 60900; VDE 0682 - 201:2005 - 01

for combined slot-head/crosshead screws in electrical equipment, e.g. terminal blocks

PZ FL 1	80	165	12	11 7751
PZ FL 2	100	195	12	11 7752
Set PZ FL 1 and PZ FL 2 (CIMCO article no. 11 7751 and 11 7752)			1	11 7750
PH FL 1	80	165	12	11 7757
PH FL 2	100	195	12	11 7758

Hex key (Allen wrench)

according to DIN EN 60900; VDE 0682 - 201:2005 - 01

Size 3	75	160	12	11 7823
Size 4	75	160	12	11 7824
Size 5	75	170	12	11 7825
Size 6	100	195	12	11 7826
Size 8	100	210	12	11 7828

TORX® screwdriver

according to DIN EN 60900; VDE 0682 - 201:2005 - 01

T 8	60	145	12	11 7908
T 9	60	145	12	11 7909
T 10	60	155	12	11 7910
T 15	75	170	12	11 7915
T 20	100	195	12	11 7920
T 25	100	195	12	11 7925
T 30	100	210	12	11 7930

Nut drivers

according to DIN EN 60900; VDE 0682 - 201:2005 - 01

Size 5.5	125	220	12	11 7805
Size 6	125	220	12	11 7806
Size 7	125	235	12	11 7807
Size 8	125	235	12	11 7808
Size 9	125	235	12	11 7809
Size 10	125	235	12	11 7810
Size 11	125	235	12	11 7811
Size 13	125	235	12	11 7813