
Ball-end magnetic bit holder

with pivoting angle up to 20°, $^{1}/_{4}$ " \times 90 mm,

for screwing applications in deep corners or other tight places. With torque-stable stainless steel casing, hardened, blasted and bronzed. Sliding casing that releases the pivoting function is plated in matt chrome and has a colour ring. Hex ball-end joint of chrome vanadium steel, stainless steel casing ø 12.0×32 mm



T-handle magnetic bit holder

in modern two-component design, for 1/4" bits of all lengths

	85 x 95	12	11 4500
--	---------	----	---------

Bit case, 10 pieces

case cap with star-shaped receiver for bits and universal holder

for slot-head screws

4 - 5.5 - 7 mm width

for Phillips crosshead screws

PH 1 - PH 2 - PH 3

for Pozidriv crosshead screws

PZ 1 - PZ 2 - PZ 3

Handy bit cases

each with a 60 mm magnetic holder. The case can also be used directly as an assembly tool.

with 6 hits

for slot-head screws $5.5 \times 0.8 - 6.5 \times 1.2$

for Phillips crosshead screws PH 1 + PH 2

for Pozidriv cross-head screws PZ 1 + PZ 2

7 pieces 11 4598

with 16 bits for slot-head screws 6.5×1.2

for Phillips crosshead screws PH 1, PH 2 (2 piece), PH 3

for Pozidriv crosshead screws PZ 1, PZ 2 (3 piece), PZ 3 for TORX $^{\text{\tiny{(8)}}}$ with bore T 10, T 15, T 20, T 25, T 30, T 40

11 4596 17 pieces

with 2 TORX® bits each of size T 10 - T 20 - T 25

7 pieces 11 4597

COMFORT bit sets

in an impact-resistant plastic box with a practical opening mechanism to provide quick access

to individual bits and magnetic bit holders

Magnetic holder 60 mm for 1/4" bit drive

for Phillips crosshead screws PH 1, PH 2

for Pozidriv cross-head screws PZ 1, PZ 2

for $TORX^{\text{®}}$ size T 15, T 20, T 25, T 30

for Slot-head screws 0.8 mm, 1.0 mm

11 4590 11 pieces

Magnetic holder 90 mm for 1/4" bit drive

Magnetic holder with quick-fit coupling 60 mm for 1/4" bit drive

for TORX $^{\text{\tiny B}}$ size T 10, 2x T 15, 2x T 20, T 25, T 30

for TORX $^{\text{\tiny{(B)}}}$ with bore size T 10, 2x T 15, 2x T 20, T 25, T 30

for cross-head screws Phillips PH 1, 3x PH 2, PH 3

for cross-head screws Pozidriv PZ 1, 3x PZ 2, PZ 3

for Hex socket 4.0 mm, 5.0 mm, 6.0 mm

Blade size $(W \times H \times L mm)$

for Slot-head screws 0.8 mm, 1.0 mm, 1.2 mm

32 pieces 11 4592













