

AC/DC voltage tester up to 690 V with LED and LCD display

- Automatic polarity detection
 - Display: 1 LCD 3 digits, 12 LEDs (+12 V, -12 V, 24 V, 50 V, 120 V, 230 V, 400 V, 690 V)
 - Continuity test with visual and acoustic display
 - Integrated single-pole testing
 - Impact-resistant modern housing
 - Bright LED display
 - Quick single lever testing at earthed contact sockets
 - Test probe protection
 - Single-pole test, continuity test
 - Automatic polarity display
 - TÜV / GS certified
 - Weight: 180 g
- Incl. 2 batteries 1.5 V AAA, LR03
 - Cable length: 1.2 m
 - Overvoltage category CAT III / IV
 - Tested in accord. with EN 61010, EN 61243-3:2010
 - Power consumption < 3.5 mA
 - Continuity test visual and acoustic
 - Protection class: IP 64
 - Measurement category: CAT IV 600 V, CAT III 1000 V
 - Single-pole test > 90 – 690 V AC
 - AC frequency range 40 - 400 Hz
 - Voltage range 12 - 690 V AC/DC
 - Integrated torch
 - ELV, rotating field L/R

240 x 65 x 19

1

11 1429



AC/DC voltage tester to 690 V with LED display

- Automatic polarity detection
 - Display: 12 LEDs (+12 V, -12 V, 24 V, 50 V, 120 V, 230 V, 400 V, 690 V)
 - Continuity test with visual and acoustic display
 - Integrated single-pole testing
 - Impact-resistant modern housing
 - Bright LED display
 - Quick single lever testing at earthed contact sockets
 - Test probe protection
 - Single-pole test, continuity test
 - Automatic polarity display
 - TÜV / GS certified
 - Weight: 170 g
- Incl. 2 batteries 1.5 V AAA, LR03
 - Cable length: 1.2 m
 - Overvoltage category CAT III / IV
 - Tested in accord. with EN 61010, EN 61243-3:2010
 - Power consumption < 3.5 mA
 - Continuity test visual and acoustic
 - Protection class: IP 64
 - Measurement category: CAT IV 600 V, CAT III 1000 V
 - Single-pole test > 90 – 690 V AC
 - AC frequency range 40 - 400 Hz
 - Voltage range 12 - 690 V AC/DC
 - Integrated torch
 - ELV, rotating field L/R

240 x 65 x 19

1

11 1432



AC/DC voltage tester to 690 V

- Automatic polarity detection
 - Display: 11 LEDs (+12 V, -12 V, 24 V, 50 V, 120 V, 230 V, 400 V, 690 V)
 - Continuity test with visual and acoustic display
 - Integrated single-pole testing
 - Impact-resistant modern housing
 - Bright LED display
 - Quick single lever testing at earthed contact sockets
 - Test probe protection
 - Single-pole test, continuity test
 - Automatic polarity display
 - TÜV / GS certified
 - Weight: 130 g
- Incl. 2 batteries 1.5 V AAA, LR03
 - Cable length: 1.2 m
 - Overvoltage category CAT III / IV
 - Tested in accord. with EN 61010, EN 61243-3:2010
 - Power consumption < 3.5 mA
 - Visual and acoustic continuity/diode test
 - Protection class: IP 64
 - Measurement category: CAT III 600 V, CAT IV 300 V
 - Single-pole test > 100 – 690 V AC
 - AC frequency range 0 - 65 Hz
 - Voltage range 12 - 690 V AC/DC
 - ELV

205 x 67 x 27

1

11 1434

