Design Size/mm PU Article no

Cable detective

Test instrument for mains copper cables, for discovering connection faults in customised data cables and complete installations. All coaxial connections with BNC/TNC connectors, USB cables and all UTP/STP cabling with 6 or 8 pin modular plugs can be checked in seconds for wire breaks, pin assignment and short circuits, both for individual conductors and for shielding.

With visual (LED) and acoustic error signals. The "Cable Detective" reduces the tedious, fraught and expensive search for cable faults to a minimum. Even longer cables laid up to 200 m can be tested by a single person. In a practical belt bag, for 9 Volt E-block battery, comprehensive operating instructions.



145 x 86 x 26 mm	1	11 1440
145 X 86 X 26 MM	i i	11 1440

Voltage tester

with clear, transparent, impact-resistance plastic haft tested according to VDE

W mm	L mm	Testing range Volt				
3.0	65	120 - 250 AC	140	12	11 1280	
3.5	100	120 - 250 AC	190	12	11 1288	



Voltage tester Drei-Ve

The innovative triangular handle means this new CIMCO voltage tester is simply easier to hold in the hand. The Drei-Ve voltage tester has an ergonomically shaped triangular handle in transparent, impact-resistant plastic. The curved vertical contour allows the best possible contact pressure and the appropriately shaped holding clip on the handle will secure it to a shirt or overall pocket. The voltage tester is manufactured to meet the latest DIN standards and VDE/GS tested.

W mm	L mm	Testing range Volt				
3.0	65	150 - 250 AC	155	1	11 1282	



Voltage tester

with clear, transparent, impact-resistance plastic haft in DIY pouch (not licensed for Germany)

W mm	L mm	Testing range Volt				
3	45	100 - 500 AC	125	12	11 1320	



Voltage tester

with retractable screwdriver blade

W mm	L mm	Test area volt				
4	25	150 - 250 AC	140	12	11 1300	



Voltage tester EURO

with surrounding anti-slip protection

W mm	L mm	Testing range Volt				
3.5	14	125 - 250 AC	190	12	11 1290	



Design Size/mm PU Article no.



81

Advice and ordering: Phone: +49 (0)2191 3718-01, Fax: +49 (0)2191 3718-85, E-mail: order@cimco.de

4

7

9

11

13

14

16

10

19

20

22

23

24

45