Design		Size	/mm	PU A	Article no.				
Cable shear									
. .	formance for copper a								
	ground cutting edges, [.] r fine wire cables up to	-		ient plastic nano	lie sieeves				
for cable ø	solid mm ²	flexible mm ²					10		
18 mm	16	50	180	1	12 0116		er.		
To min	10	50	100		12 0110		-		
One-hand c	able shears								
	formance for copper a	nd aluminium (cable, smooth, no	n-deforming cu	ıt, 🚺	$\textcircled{\bullet}$			
	ground, adjustable sci								
for cable ø	solid mm ²	flexible mm ²					- All		
16 mm	16	50	160	6	12 0104		er fa		
1000 V .									
	and cable sh								
÷.	formance for copper a		cable, smooth, nc	on-deforming	EC62300 2004				
	-coated special insulation								
for cable ø	solid mm ²	flexible mm ²		,	42.0207		DO'A		
16 mm	16	50	160	6	12 0206				
One-hand c	able shears								
	ormance for copper an	id aluminium ca	ble, smooth, non-	-deforming cut		$(\textcircled{\bullet})$			
÷.	ground, adjustable sci			-	s				10
for cable ø	solid mm ²	flexible mm ²					The state		
25 mm	25	70	200	6	12 0100		2 Al		
1000 V									
	and cable sh								
	formance for copper a		cable, smooth, nc	on-deforming					
	coated special insulation								
for cable ø 25 mm	solid mm ² 25	flexible mm ² 70	200	6	12 0202		Jo!A		
25 11111	23	70	200	0	12 0202				
Cable shear									
	rs for copper, aluminiu i-core cables up to 12								
	one on the cutting head								
plastic handle sleeve		1) and precise	cutting of cables.	vvitil ergonomi	cally shaped 2 comp	Donent			
Weight 300 g.	5.						The lot		
11018110000 81			200	1	12 0138		STA		
Insulation s	tripping cab	le shears	5						
	rs for copper and alumi					\bullet			
Insulation stripping fu	nction can be set with a	a screw for adju	sting to the desire	d wire or flex d	iameter from 0.5 to 2	2.0 mm			
	cutting head). This too	l is suitable for	stripping 4 - 16 m	m (in the cuttin	g area) and for preci	ision			
cutting of cables. Wit	h single-dip coating.						OI P		
			160	1	12 0242				
Cable shear	* 6					\bigcirc			
		im and convict	cables This tas!	c cuitable fam					
	rs for copper, aluminiu ables, handles with sin			S SUILADIE IOI					
12 mm ø or 70 mm		Sic cip coaung	. 240	1	12 0330		N.S.S.		
20 mm ø or 95 mm			240	1	12 0330		e		
			200		12 00 10				
Cable shear	rs								
Universal cable shea	rs for copper, aluminiu	ım and coaxial	cables. This tool i	s suitable for		\bullet			
	nsulation (special zone	e on the cutting	ghead) and precis	sion cutting of c	ables.		- P		
Handles with single-							2		
10 mm ø or 50 mn	n-		160	1	12 0332				
Design		Size	/mm	PU /	Article no.			:imco°	