

Data Sheet | Item Number: 790-134

Busbar; tin-plated; 50 mm long; Cu 10 mm x 3 mm; silver-colored

<https://www.wago.com/790-134>



Color: silver-colored

Material data

Color	silver-colored
Fire load	0 MJ
Weight	13.5 g

Commercial data

eCl@ss 10.0	27-14-11-39
eCl@ss 9.0	27-14-11-39
ETIM 9.0	EC001522
ETIM 8.0	EC001522
PU (SPU)	20 pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454229740
Customs tariff number	7407100000

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product
Compliance 790-134



Documentation

Bid Text			
790-134	19.02.2019	xml 2.54 KB	
790-134	28.11.2018	doc 23.00 KB	

CAD/CAE-Data

CAD data	CAE data
2D/3D Models 790-134	EPLAN Data Portal 790-134
	WSCAD Universe 790-134
	ZUKEN Portal 790-134

1 Compatible Products

1.1 Optional Accessories

1.1.1 Shield termination

1.1.1.1 Shield clamping saddles

Item No.: 790-108 Shield clamping saddle; 11 mm wide; diameter of compatible conductor; 3 ... 8 mm	Item No.: 790-208 Shield clamping saddle; 12.4 mm wide; 3 ... 8 mm	Item No.: 790-116 Shield clamping saddle; 19 mm wide; diameter of compatible conductor; 7 ... 16 mm	Item No.: 790-216 Shield clamping saddle; 21.8 mm wide; 6 ... 16 mm
Item No.: 790-124 Shield clamping saddle; 27 mm wide; diameter of compatible conductor; 6 ... 24 mm	Item No.: 790-220 Shield clamping saddle; 30 mm wide; 6 ... 20 mm	Item No.: 790-140 Shield clamping saddle; diameter of compatible conductor	

1.1.1.2 Shield termination

Item No.: 791-107 Shield clamp; diameter of compatible conductor; 1.5 mm to 6.5 mm; H max. 40 mm; 10 mm wide	Item No.: 791-117 Shield clamp; diameter of compatible conductor; 10 mm to 17 mm; H max. 63 mm; 23 mm wide	Item No.: 791-124 Shield clamp; diameter of compatible conductor; 16 mm to 24 mm; H max. 78 mm; 30 mm wide	Item No.: 791-111 Shield clamp; diameter of compatible conductor; 5 mm to 11 mm; H max. 47 mm; 17 mm wide

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: www.wago.com