

Color: ■ white

### Technical data

Marking method	Thermal transfer
Marking	plain
Delivery form	Roll
Delivery form configuration	1,000 pcs/reel
Printing device	Smart Printer (thermal transfer printer)

### Physical data

Depth	0.12 mm
Marking surface	12 x 23 mm

### Mechanical data

Mounting type	Wrapping
Smear resistance	in conjunction with 258-5014 Ink Ribbon

### Material data

Color	white
Material	Polyvinyl chloride
UV resistance	EN 60068-2-5:2010 Procedure B
Adhesive information	Acrylic; permanent
Halogen-free	Yes
Weight	181 g
Fire load	0 MJ

Environmental requirements	
Ambient temperature (storage)	+10 ... +22 °C
Ambient temperature (operation)	-30 ... +120 °C
Relative humidity	40 ... 50 %

Commercial data	
Product Group	2 (Terminal Block Accessories)
eCl@ss 10.0	27-40-04-01
eCl@ss 9.0	27-40-06-29
ETIM 9.0	EC001530
ETIM 8.0	EC001530
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	DE
GTIN	4050821656869
Customs tariff number	39191080888

Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

## Downloads

### Environmental Product Compliance

Compliance Search	
Environmental Product Compliance 211-856	<a href="#">↓</a>

## Documentation

Operating Instructions			
211-856 Information on printing material	1	pdf	<a href="#">↓</a>
	28.08.2020	1316.17 KB	

## 1 Compatible Products

### 1.1 Optional Accessories

#### 1.1.1 Marking

##### 1.1.1.1 Marking device



**Item No.: 258-5000**  
 Thermal transfer printer; Smart Printer; for complete control cabinet marking; 300 dpi; With marking material

## Installation Notes


### Marking



Remove the printed label from the sheet or reel.



Wrap the label around the conductor or cable.



The transparent laminate protects the marking.