


## Data sheet

Commercial Art.No.: R1.541.1050.0

light curtain SLC-4TR14-1050

Safety-Lightcurtain Type 4, Transmitter, Resolution 14 mm, L = 1050 mm



|                    |               |
|--------------------|---------------|
| Commercial Art.No. | R1.541.1050.0 |
| EAN                | 4049088202483 |
| Order Unit         | 1             |

certificates / approvals



## Technical data

### function

|                      |                  |
|----------------------|------------------|
| sensor element       | Transmitter      |
| with muting function | no               |
| with muting display  | no               |
| muting with          | samosPRO COMPACT |
| with beam coding     | no               |
| automatic start      | no               |
| restart interlock    | no               |
| alignment aid        | no               |
| blanking             | no               |
| cascadable           | no               |

### technical data

|                                     |               |
|-------------------------------------|---------------|
| type acc. EN 61496-1                | 4             |
| resolution                          | 14 mm         |
| protective field height             | 1050 mm       |
| distance                            | 0 - 6 m       |
| connection                          | connector M12 |
| nominal voltage                     | 24 V          |
| voltage type                        | DC            |
| number of OSSD outputs              | 2             |
| max. output current                 | 380 mA        |
| degree of protection (IP)           | IP65          |
| PFH <sub>d</sub> (High demand mode) | 7.73 E-9 1/h  |
| mission time TM                     | 20 a          |

### safety parameters

|                        |         |
|------------------------|---------|
| category (ISO 13849-1) | 4       |
| PL (ISO 13849-1)       | level e |

|                                     |              |
|-------------------------------------|--------------|
| SIL <sub>CL</sub> (IEC 62061)       | 3            |
| PFH <sub>d</sub> (High demand mode) | 7.73 E-9 1/h |
| HFT                                 | 1            |
| T <sub>M</sub>                      | 20 a         |

#### dimensions

|                  |         |
|------------------|---------|
| width sensor     | 29 mm   |
| height of sensor | 35.4 mm |
| length of sensor | 1116 mm |

#### classification

|            |          |
|------------|----------|
| ECLASS 11  |          |
| ECLASS 8.1 | 27270910 |
| ETIM 9.0   | EC002549 |
| ETIM 8.0   | EC002549 |
| ETIM 7.0   | EC002549 |
| ETIM 6.0   | EC002549 |
| ETIM 5.0   | EC002549 |
| ETIM 4.0   | EC002549 |
| ETIM 3.0   | EC002549 |

#### product compliance

|                              |           |
|------------------------------|-----------|
| ROHS conformity status       | compliant |
| REACH-SVHC conformity status | compliant |

## Accessories

| Commercial Art.No.: | Article-type description:                     | Description:  |
|---------------------|---|---|
| R1.594.1300.0       | tilted mirror tie bar SLX-COLM-1300           | Reflector column, persistant 1300 mm                              |
| R1.596.1430.0       | test bar SLX-ACC-TEST1430                     | Test bar, 14/30 mm  |
| R1.596.2040.0       | test bar SLX-ACC-TEST2040                     | Test bar, 20/40 mm  |
| R1.500.0505.0       | connection cable SLX-CAB-M12-0505             | SLC M12, 5 pin Connection Cable (unshielded), 5m long             |
| R1.500.0510.0       | connection cable SLX-CAB-M12-0510             | Connection cable M12, 5-pole, Length 10m, unshielded              |
| R1.500.0515.0       | connection cable SLX-CAB-M12-0515             | Connection cable M12, 5-pole, Length 15m, unshielded              |
| R1.500.0525.0       | connection cable SLX-CAB-M12-0525             | Connection cable M12, 5-pole, Length 25m, unshielded              |
| R1.500.0550.0       | connection cable SLX-CAB-M12-0550             | Connection cable M12, 5-pole, Length 50m, unshielded              |
| R1.600.0505.0       | connection cable SLX-CAB-M12-S0505            | Connection cable M12, 5-pole, Length 5m, shielded                 |
| R1.600.0510.0       | connection cable SLX-CAB-M12-S0510            | Connection cable M12, 5-pole, Length 10m, shielded                |
| R1.600.0515.0       | connection cable SLX-CAB-M12-S0515            | Connection cable M12, 5-pole, Length 15m, shielded                |
| R1.600.0525.0       | connection cable SLX-CAB-M12-S0525            | Connection cable M12, 5-pole, Length 25m, shielded                |
| R1.600.0550.0       | connection cable SLX-CAB-M12-S0550            | Connection cable M12, 5-pole, Length 50m, shielded                |
| R1.593.1300.0       | device columns SLX-COL-1300                   | "Device column, profile heighth: 1280 mm; Total heighth: 1360 mm" |
| R1.591.0001.0       | sliding block set SLX-MO-TNUTM6               | Set Slot nut with M6-screw thread, 10 pcs.                        |
| R1.591.0005.0       | Z-fixture SLX-MO-Z                            | Z-Bracket, 2 pcs.   |
| R1.591.0007.0       | rotary holding with shockabsorber SLX-MO-RO-S | Rotative bracket with Shockabsorber, 70mm lang, 2 pcs.            |
| R1.591.0009.0       | tool holder SLX-MO-CLIP                       | Clamp bracket, for Installation in Device column                  |
| R1.591.0010.0       | set tool holder SLX-MO-CLIP2                  | Set Clamp bracket, for Installation in Device column              |
| R1.591.0020.0       | rotary holding 360° SLX-MO-RO2                | Rotative bracket, 2 pcs., incl. 1 pcs. SLC-cylinder               |

**Fits with**

| <b>Commercial Art.No.:</b> | <b>Article-type description:</b> | <b>Description:</b>  |
|----------------------------|----------------------------------|--|
| R1.551.1050.0              | light curtain SLC-4ST14-1050     | Safety-Lightcurtain Type 4, Receiver-Standard, Resolution 14 mm, L = 1050 mm     |
| R1.571.1050.0              | light curtain SLC-4PR14-1050     | Safety-Lightcurtain Type 4, Receiver-Professional, Resolution 14 mm, L = 1050 mm |

SLC 2 - Sender / transmitter

| Schutzfeldhöhe / Protective field height (mm) | Länge / length (mm) | Auflösung / resolution 20 mm | Auflösung / resolution 30 mm | Auflösung / resolution 40 mm | Auflösung / resolution 90 mm |
|---|---------------------|------------------------------|------------------------------|------------------------------|------------------------------|
| 150   | 216                 | R1.512.0150.0                | R1.513.0150.0                | R1.514.0150.0                | -                            |
| 225   | 291                 | R1.512.0225.0                | R1.513.0225.0                | R1.514.0225.0                | -                            |
| 300   | 366                 | R1.512.0300.0                | R1.513.0300.0                | R1.514.0300.0                | -                            |
| 450   | 516                 | R1.512.0450.0                | R1.513.0450.0                | R1.514.0450.0                | -                            |
| 600   | 666                 | R1.512.0600.0                | R1.513.0600.0                | R1.514.0600.0                | R1.515.0600.0                |
| 750   | 816                 | R1.512.0750.0                | R1.513.0750.0                | R1.514.0750.0                | R1.515.0750.0                |
| 900   | 966                 | R1.512.0900.0                | R1.513.0900.0                | R1.514.0900.0                | R1.515.0900.0                |
| 1050  | 1116                | R1.512.1050.0                | R1.513.1050.0                | R1.514.1050.0                | R1.515.1050.0                |
| 1200  | 1266                | R1.512.1200.0                | R1.513.1200.0                | R1.514.1200.0                | R1.515.1200.0                |
| 1350  | 1416                | R1.512.1350.0                | R1.513.1350.0                | R1.514.1350.0                | R1.515.1350.0                |
| 1500  | 1566                | R1.512.1500.0                | R1.513.1500.0                | R1.514.1500.0                | R1.515.1500.0                |
| 1650  | 1716                | R1.512.1650.0                | R1.513.1650.0                | R1.514.1650.0                | R1.515.1650.0                |
| 1800  | 1866                | R1.512.1800.0                | R1.513.1800.0                | R1.514.1800.0                | R1.515.1800.0                |

SLC 2 - Empfänger Standard / receiver standard

| Schutzfeldhöhe / Protective field height (mm) | Länge / length (mm) | Auflösung / resolution 20 mm | Auflösung / resolution 30 mm | Auflösung / resolution 40 mm | Auflösung / resolution 90 mm |
|---|---------------------|------------------------------|------------------------------|------------------------------|------------------------------|
| 150   | 216                 | R1.522.0150.0                | R1.523.0150.0                | R1.524.0150.0                | -                            |
| 225   | 291                 | R1.522.0225.0                | R1.523.0225.0                | R1.524.0225.0                | -                            |
| 300   | 366                 | R1.522.0300.0                | R1.523.0300.0                | R1.524.0300.0                | -                            |
| 450   | 516                 | R1.522.0450.0                | R1.523.0450.0                | R1.524.0450.0                | -                            |
| 600   | 666                 | R1.522.0600.0                | R1.523.0600.0                | R1.524.0600.0                | R1.525.0600.0                |
| 750   | 816                 | R1.522.0750.0                | R1.523.0750.0                | R1.524.0750.0                | R1.525.0750.0                |
| 900   | 966                 | R1.522.0900.0                | R1.523.0900.0                | R1.524.0900.0                | R1.525.0900.0                |
| 1050  | 1116                | R1.522.1050.0                | R1.523.1050.0                | R1.524.1050.0                | R1.525.1050.0                |
| 1200  | 1266                | R1.522.1200.0                | R1.523.1200.0                | R1.524.1200.0                | R1.525.1200.0                |
| 1350  | 1416                | R1.522.1350.0                | R1.523.1350.0                | R1.524.1350.0                | R1.525.1350.0                |
| 1500  | 1566                | R1.522.1500.0                | R1.523.1500.0                | R1.524.1500.0                | R1.525.1500.0                |
| 1650  | 1716                | R1.522.1650.0                | R1.523.1650.0                | R1.524.1650.0                | R1.525.1650.0                |
| 1800  | 1866                | R1.522.1800.0                | R1.523.1800.0                | R1.524.1800.0                | R1.525.1800.0                |

SLC 2 - Empfänger Select / receiver select

| Schutzfeldhöhe / Protective field height (mm) | Länge / length (mm) | Auflösung / resolution 20 mm | Auflösung / resolution 30 mm | Auflösung / resolution 40 mm | Auflösung / resolution 90 mm |
|---|---------------------|------------------------------|------------------------------|------------------------------|------------------------------|
| 150   | 216                 | R1.532.0150.0                | R1.533.0150.0                | R1.534.0150.0                | -                            |
| 225   | 291                 | R1.532.0225.0                | R1.533.0225.0                | R1.534.0225.0                | -                            |
| 300   | 366                 | R1.532.0300.0                | R1.533.0300.0                | R1.534.0300.0                | -                            |
| 450   | 516                 | R1.532.0450.0                | R1.533.0450.0                | R1.534.0450.0                | -                            |
| 600   | 666                 | R1.532.0600.0                | R1.533.0600.0                | R1.534.0600.0                | R1.535.0600.0                |
| 750   | 816                 | R1.532.0750.0                | R1.533.0750.0                | R1.534.0750.0                | R1.535.0750.0                |
| 900   | 966                 | R1.532.0900.0                | R1.533.0900.0                | R1.534.0900.0                | R1.535.0900.0                |
| 1050  | 1116                | R1.532.1050.0                | R1.533.1050.0                | R1.534.1050.0                | R1.535.1050.0                |
| 1200  | 1266                | R1.532.1200.0                | R1.533.1200.0                | R1.534.1200.0                | R1.535.1200.0                |
| 1350  | 1416                | R1.532.1350.0                | R1.533.1350.0                | R1.534.1350.0                | R1.535.1350.0                |
| 1500  | 1566                | R1.532.1500.0                | R1.533.1500.0                | R1.534.1500.0                | R1.535.1500.0                |
| 1650  | 1716                | R1.532.1650.0                | R1.533.1650.0                | R1.534.1650.0                | R1.535.1650.0                |
| 1800  | 1866                | R1.532.1800.0                | R1.533.1800.0                | R1.534.1800.0                | R1.535.1800.0                |

SLC 4 - Sender / transmitter

| Schutzfeldhöhe / Protective field height (mm) | Länge / length (mm) | Auflösung / resolution 14 mm | Auflösung / resolution 20 mm | Auflösung / resolution 30 mm | Auflösung / resolution 40 mm | Auflösung / resolution 90 mm |
|---|---------------------|------------------------------|------------------------------|------------------------------|------------------------------|------------------------------|
| 150   | 216                 | R1.541.0150.0                | R1.542.0150.0                | R1.543.0150.0                | R1.544.0150.0                | -                            |
| 225   | 291                 | -                            | R1.542.0225.0                | R1.543.0225.0                | R1.544.0225.0                | -                            |
| 300   | 366                 | R1.541.0300.0                | R1.542.0300.0                | R1.543.0300.0                | R1.544.0300.0                | -                            |
| 450   | 516                 | R1.541.0450.0                | R1.542.0450.0                | R1.543.0450.0                | R1.544.0450.0                | -                            |
| 600   | 666                 | R1.541.0600.0                | R1.542.0600.0                | R1.543.0600.0                | R1.544.0600.0                | R1.545.0600.0                |
| 750   | 816                 | R1.541.0750.0                | R1.542.0750.0                | R1.543.0750.0                | R1.544.0750.0                | R1.545.0750.0                |
| 900   | 966                 | R1.541.0900.0                | R1.542.0900.0                | R1.543.0900.0                | R1.544.0900.0                | R1.545.0900.0                |
| 1050  | 1116                | R1.541.1050.0                | R1.542.1050.0                | R1.543.1050.0                | R1.544.1050.0                | R1.545.1050.0                |
| 1200  | 1266                | R1.541.1200.0                | R1.542.1200.0                | R1.543.1200.0                | R1.544.1200.0                | R1.545.1200.0                |
| 1350  | 1416                | R1.541.1350.0                | R1.542.1350.0                | R1.543.1350.0                | R1.544.1350.0                | R1.545.1350.0                |
| 1500  | 1566                | R1.541.1500.0                | R1.542.1500.0                | R1.543.1500.0                | R1.544.1500.0                | R1.545.1500.0                |
| 1650  | 1716                | R1.541.1650.0                | R1.542.1650.0                | R1.543.1650.0                | R1.544.1650.0                | R1.545.1650.0                |
| 1800  | 1866                | R1.541.1800.0                | R1.542.1800.0                | R1.543.1800.0                | R1.544.1800.0                | R1.545.1800.0                |


SLC 4 - Empfänger Standard / receiver standard

| Schutzfeldhöhe / Protective field height (mm) | Länge / length (mm) | Auflösung / resolution 14 mm | Auflösung / resolution 20 mm | Auflösung / resolution 30 mm | Auflösung / resolution 40 mm | Auflösung / resolution 90 mm |
|---|---------------------|------------------------------|------------------------------|------------------------------|------------------------------|------------------------------|
| 150   | 216                 | R1.551.0150.0                | R1.552.0150.0                | R1.553.0150.0                | R1.554.0150.0                | -                            |
| 225   | 291                 | -                            | R1.552.0225.0                | R1.553.0225.0                | R1.554.0225.0                | -                            |
| 300   | 366                 | R1.551.0300.0                | R1.552.0300.0                | R1.553.0300.0                | R1.554.0300.0                | -                            |
| 450   | 516                 | R1.551.0450.0                | R1.552.0450.0                | R1.553.0450.0                | R1.554.0450.0                | -                            |
| 600   | 666                 | R1.551.0600.0                | R1.552.0600.0                | R1.553.0600.0                | R1.554.0600.0                | R1.555.0600.0                |
| 750   | 816                 | R1.551.0750.0                | R1.552.0750.0                | R1.553.0750.0                | R1.554.0750.0                | R1.555.0750.0                |
| 900   | 966                 | R1.551.0900.0                | R1.552.0900.0                | R1.553.0900.0                | R1.554.0900.0                | R1.555.0900.0                |
| 1050  | 1116                | R1.551.1050.0                | R1.552.1050.0                | R1.553.1050.0                | R1.554.1050.0                | R1.555.1050.0                |
| 1200  | 1266                | R1.551.1200.0                | R1.552.1200.0                | R1.553.1200.0                | R1.554.1200.0                | R1.555.1200.0                |
| 1350  | 1416                | R1.551.1350.0                | R1.552.1350.0                | R1.553.1350.0                | R1.554.1350.0                | R1.555.1350.0                |
| 1500  | 1566                | R1.551.1500.0                | R1.552.1500.0                | R1.553.1500.0                | R1.554.1500.0                | R1.555.1500.0                |
| 1650  | 1716                | R1.551.1650.0                | R1.552.1650.0                | R1.553.1650.0                | R1.554.1650.0                | R1.555.1650.0                |
| 1800  | 1866                | R1.551.1800.0                | R1.552.1800.0                | R1.553.1800.0                | R1.554.1800.0                | R1.555.1800.0                |

SLC 4 - Empfänger Select / receiver select

| Schutzfeldhöhe / Protective field height (mm) | Länge / length (mm) | Auflösung / resolution 14 mm | Auflösung / resolution 20 mm | Auflösung / resolution 30 mm | Auflösung / resolution 40 mm | Auflösung / resolution 90 mm |
|---|---------------------|------------------------------|------------------------------|------------------------------|------------------------------|------------------------------|
| 150   | 216                 | R1.561.0150.0                | R1.562.0150.0                | R1.563.0150.0                | R1.564.0150.0                | -                            |
| 225   | 291                 | -                            | R1.562.0225.0                | R1.563.0225.0                | R1.564.0225.0                | -                            |
| 300   | 366                 | R1.561.0300.0                | R1.562.0300.0                | R1.563.0300.0                | R1.564.0300.0                | -                            |
| 450   | 516                 | R1.561.0450.0                | R1.562.0450.0                | R1.563.0450.0                | R1.564.0450.0                | -                            |
| 600   | 666                 | R1.561.0600.0                | R1.562.0600.0                | R1.563.0600.0                | R1.564.0600.0                | R1.565.0600.0                |
| 750   | 816                 | R1.561.0750.0                | R1.562.0750.0                | R1.563.0750.0                | R1.564.0750.0                | R1.565.0750.0                |
| 900   | 966                 | R1.561.0900.0                | R1.562.0900.0                | R1.563.0900.0                | R1.564.0900.0                | R1.565.0900.0                |
| 1050  | 1116                | R1.561.1050.0                | R1.562.1050.0                | R1.563.1050.0                | R1.564.1050.0                | R1.565.1050.0                |
| 1200  | 1266                | R1.561.1200.0                | R1.562.1200.0                | R1.563.1200.0                | R1.564.1200.0                | R1.565.1200.0                |
| 1350  | 1416                | R1.561.1350.0                | R1.562.1350.0                | R1.563.1350.0                | R1.564.1350.0                | R1.565.1350.0                |
| 1500  | 1566                | R1.561.1500.0                | R1.562.1500.0                | R1.563.1500.0                | R1.564.1500.0                | R1.565.1500.0                |
| 1650  | 1716                | R1.561.1650.0                | R1.562.1650.0                | R1.563.1650.0                | R1.564.1650.0                | R1.565.1650.0                |
| 1800  | 1866                | R1.561.1800.0                | R1.562.1800.0                | R1.563.1800.0                | R1.564.1800.0                | R1.565.1800.0                |

Qu - PEE 12/92



|   |   |  |   |
|---|---|--|---|
| Weitere Angaben siehe KATALOG oder eKatalog.<br>Additional data see CATALOG or eCatalog.  |   | www.wieland-electric.com<br>eshop.wieland-electric.com                                   |   |
| ja/yes <input checked="" type="checkbox"/> Stoffverbots- und Deklarationsliste nach WN 5020.010 ist einzuhalten.<br>Conformity with Wieland document WN 5020.010 e (list of prohibited / declarable hazardous substances) to be declared! |   |  |   |
| Freitoleranz nach<br>General tolerance  | CAD-Zeichnung, keine manuellen Änderungen<br>CAD drawing, no manual modifications allowed | 1. Verwendung:<br>First Use:   | Blatt:<br>Sheet:  |
|   | Werkstoff / Material  | 2015<br>gezeichnet<br>drawn<br>30.04.<br>geprüft<br>checked<br>Normgepr.<br>Stand. check | Name<br>Kötzner   |
|   | Maßstab/Scale   | Zeichnung Nr. / Drawing No.<br><b>T R1.512.0150.0 01K</b>                                |   |
|   | Maße in mm / Dimensions are in mm   |  |   |
|   | Datei / File: 40631__01K.DCD  | Ersatz für / Replacement for:  |   |
|   |   | Type   | Benennung / Title<br>Teilespezifikation /<br>Component specification<br><b>Lichtvorhang SLC /<br/>light curtain SLC</b> |
| Index   | Datum / Blatt<br>Date / Sheet   | www.wieland<br>www.wieland-electric.com  |   |
| Änderung / Revision   |   |  |   |

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Die Reproduktion, Distribution und Nutzung dieses Dokuments sowie die Kommunikation der Inhalte mit anderen ohne schriftliche Genehmigung ist prohibited.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
M1  
M2  
M3  
L  
G  
i  
11.1  
12.1  
1.1