


Data sheet

Commercial Art.No.: R1.551.1050.0

light curtain SLC-4ST14-1050

Safety-Lightcurtain Type 4, Receiver-Standard, Resolution 14 mm, L = 1050 mm



Commercial Art.No.	R1.551.1050.0
EAN	4049088202247
Order Unit	1

certificates / approvals



Technical data

function

sensor element	
with muting function	no
with muting display	no
muting with	samosPRO COMPACT
with beam coding	yes
automatic start	yes
restart interlock	no
alignment aid	no
blanking	no
cascadable	no

technical data

type acc. EN 61496-1	4
resolution	14 mm
protective field height	1050 mm
distance	0 - 6 m
connection	connector M12
nominal voltage	24 V
voltage type	DC
number of OSSD outputs	2
max. output current	380 mA
degree of protection (IP)	IP65
PFH _d (High demand mode)	7.73 E-9 1/h
mission time TM	20 a

safety parameters

category (ISO 13849-1)	4
PL (ISO 13849-1)	level e

SIL _{CL} (IEC 62061)	3
PFH _d (High demand mode)	7.73 E-9 1/h
HFT	1
T _M	20 a

dimensions

width sensor	29 mm
height of sensor	35.4 mm
length of sensor	1116 mm

classification

ECLASS 11	
ECLASS 8.1	27270910
ETIM 9.0	EC002549
ETIM 8.0	EC002549
ETIM 7.0	EC002549
ETIM 6.0	EC002549
ETIM 5.0	EC002549
ETIM 4.0	EC002549
ETIM 3.0	EC002549

product compliance

ROHS conformity status	compliant
REACH-SVHC conformity status	compliant

Accessories

Commercial Art.No.:	Article-type description:	Description:
R1.594.1300.0	tilted mirror tie bar SLX-COLM-1300	Reflector column, persistant 1300 mm
R1.596.1430.0	test bar SLX-ACC-TEST1430	Test bar, 14/30 mm
R1.596.2040.0	test bar SLX-ACC-TEST2040	Test bar, 20/40 mm
R1.500.0505.0	connection cable SLX-CAB-M12-0505	SLC M12, 5 pin Connection Cable (unshielded), 5m long
R1.500.0510.0	connection cable SLX-CAB-M12-0510	Connection cable M12, 5-pole, Length 10m, unshielded
R1.500.0515.0	connection cable SLX-CAB-M12-0515	Connection cable M12, 5-pole, Length 15m, unshielded
R1.500.0525.0	connection cable SLX-CAB-M12-0525	Connection cable M12, 5-pole, Length 25m, unshielded
R1.500.0550.0	connection cable SLX-CAB-M12-0550	Connection cable M12, 5-pole, Length 50m, unshielded
R1.600.0505.0	connection cable SLX-CAB-M12-S0505	Connection cable M12, 5-pole, Length 5m, shielded
R1.600.0510.0	connection cable SLX-CAB-M12-S0510	Connection cable M12, 5-pole, Length 10m, shielded
R1.600.0515.0	connection cable SLX-CAB-M12-S0515	Connection cable M12, 5-pole, Length 15m, shielded
R1.600.0525.0	connection cable SLX-CAB-M12-S0525	Connection cable M12, 5-pole, Length 25m, shielded
R1.600.0550.0	connection cable SLX-CAB-M12-S0550	Connection cable M12, 5-pole, Length 50m, shielded
R1.593.1300.0	device columns SLX-COL-1300	"Device column, profile heighth: 1280 mm; Total heighth: 1360 mm"
R1.591.0001.0	sliding block set SLX-MO-TNUTM6	Set Slot nut with M6-screw thread, 10 pcs.
R1.591.0005.0	Z-fixture SLX-MO-Z	Z-Bracket, 2 pcs.
R1.591.0007.0	rotary holding with shockabsorber SLX-MO-RO-S	Rotative bracket with Shockabsorber, 70mm lang, 2 pcs.
R1.591.0009.0	tool holder SLX-MO-CLIP	Clamp bracket, for Installation in Device column
R1.591.0010.0	set tool holder SLX-MO-CLIP2	Set Clamp bracket, for Installation in Device column
R1.591.0020.0	rotary holding 360° SLX-MO-RO2	Rotative bracket, 2 pcs., incl. 1 pcs. SLC-cylinder

Fits with

Commercial Art.No.:	Article-type description:	Description:
R1.541.1050.0	light curtain SLC-4TR14-1050	Safety-Lightcurtain Type 4, Transmitter, Resolution 14 mm, L = 1050 mm

