

EPIC® MC module: HC3

The mixed assembly guarantees high flexibility. For applications in machine and plant engineering, for robotics and slide-in technology.


The power and signal module can be combined in one housing and is suitable for printing presses and investment construction.


Info

Very high current transfer in a small space













Supplementary automation components from Lapp



Mechanical and plant engineering



Wind Energy

Benefits

The mix of different functions in one plug guarantees high flexibility Assembly of individual connectors, suitable for different applications

Application range

Plant engineering Printing machines Control engineering

Technical Data

Classification ETIM 5: ETIM 5.0 Class-ID: EC002641

ETIM 5.0 Class-Description: Modular connector (industrial

connector)

Classification ETIM 6: ETIM 6.0 Class-ID: EC002641

ETIM 6.0 Class-Description: Modular connector (industrial

connector)

Rated voltage (V): IEC: 1000 V AC/DC

Last Update (25.10.2024)
©2024 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16





EPIC® MC module: HC3

UL: 600 V AC/DC

Rated current (A): 50 A
Pollution degree: 3

Contact resistance: < 2 mOhm

Contacts: Copper alloy, hard silver-plated

Number of contacts: 3

Termination methods: Crimp termination: 1.5 - 10 mm²

Cycle of mechanical operation: 100

VDE-tested: UL-tested:

UL File Number: E75770

Temperature range: -40 °C to +100 °C, short-term up to +125 °C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.



EPIC® MC module: HC3

Article number Article description Contact type Number of operating contacts Slots Packaging unit Module: high voltage 3-pin 10399800 MCS 3 CM-HV male 3 1 1 10 10399900 MCB 3 CM-HV female 3 1 1 10