

Innovative metal and plastic housing design

The robust compact plastic housing has a side cable entry and is suitable for use in machine and device manufacturing.

#### Info

Lightweight, chemically resistant plastic housing Protection rating UL50E tested











Mechanical and plant engineering



Mechanical resistance



Robust



Waterproof

### **Benefits**

Housing in plastic or metal version for safe connections in the smallest possible space

## **Application range**

Machine and equipment manufacturing Control engineering Electronic laboratory

## **Product features**

Hood Bolts for single lever Side cable entry Versions with / without cable gland

Last Update (11.11.2024)
©2024 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02\_03.16





**Technical Data** 

Classification ETIM 5: ETIM 5.0 Class-ID: EC000437

ETIM 5.0 Class-Description: Housing for industrial connectors

Classification ETIM 6: ETIM 6.0 Class-ID: EC000437

ETIM 6.0 Class-Description: Housing for industrial connectors

Material: thermoplastic, grey, black

Lever: zinc-plated steel

Protection rating: IP 65 (latched)

NEMA 250, UL50E: 12, 4 (latched)

VDE-tested: Certified production control: VDE-REG. no.: B437

UL-tested:

UL File Number: E75770

Temperature range: -40°C to +100°C, short-term up to +125°C

### Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.

Article number	Article description	М	PG	Material	Colour	Cable gland	Cable clamping range	Pieces / PU
10427300	H-A 3 Ts	-	11	Thermoplastic	black	-	-	10
10427000	H-A 3 Ts	-	11	Thermoplastic	grey	-	-	10
10620600	H-A 3 Ts	-	11	Thermoplastic	black	yes	6.5 - 12	10
10427100	H-A 3 Ts	-	11	Thermoplastic	grey	yes	6.5 - 12	10
19427300	H-A 3 MTSV 7-13	20	-	Thermoplastic	black	-	-	10
19427000	H-A 3 MTSV 7-13	20	-	Thermoplastic	grey	-	-	10



