



ETHERLINE® Cat.6_A

Fixed installation



Info

- Industrial Ethernet cable
- For PROFINET applications with 4 pairs
- CAT.6_A qualified for 10Gbit/s

Benefits

- Can be used in dry or damp rooms
- Screened against interference
- Can be used for Industrial Ethernet in harsh industrial environments
- 4pair: 100Mbit/s up to 10 Gbit/s for Industrial Ethernet

Application range

- For industrial secondary and tertiary cabling according to EN 50173-3 ISO/IEC 24702
- Wiring of machines, tools, devices, appliances and control cabinets
- Max. cable length for 100 Mbit/s is 100 m
max. cable length for 10 Gbit/s is 100 m
- Suitable for EtherCAT and EtherNet/IP applications

Product features

- PUR outer sheath is highly resistant to mineral oils and abrasion
- Robust, halogen-free outer sheath
- The oil-resistant PVC sheath enables usage in industrial environments
- High-quality, double screening ensures high transmission reliability in areas with electromagnetic interference

Product Make-up

- Solid bare copper wire AWG22
- Core insulation made of polyethylene (PE)
- S/FTP: copper braid as overall screening and pair screening with aluminium compound foil
- Colour: green (based on RAL 6018)

Technical data



ETIM 5.0 Class-ID: EC000830
ETIM 5.0 Class-Description: Data cable



Peak operating voltage
(not for power applications) 125 V



Minimum bending radius
Fixed installation: 10 x outer diameter



Characteristic impedance
100 ohm at 1 - 100 MHz



Temperature range
cable with PUR jacket
Fixed installation: VDE -30°C to +80°C;
UL/CSA -30°C to +80°C
flexing: VDE -5°C to +50°C;
UL/CSA -5°C to +80°C
cable halogenfree compound
Fixed installation: -25°C to +80°C
cable with PVC jacket
Fixed installation: -40°C to +80°C

Article number	Article designation	Number of pairs and AWG per conductor	Max. outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
Halogen-free jacket					
2170466	ETHERLINE® Cat.6 _A H	4 x 2 x AWG22/1	9.0	53	99
PUR outer sheath, halogen-free					
2170465	ETHERLINE® CAT.6 _A P	4 x 2 x AWG22/1	9.0	53	91
PVC outer sheath					
2170464	ETHERLINE® Cat.6 _A Y	4 x 2 x AWG22/1	9.0	53	98

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

PROFINET® is a registered trademark of the PNO (PROFIBUS user organisation)

Photographs are not to scale and do not represent detailed images of the respective products.

Accessories

- EPIC® DATA AX RJ45 Cat.6_A refer to page 462
- EPIC® DATA 90 RJ45 Cat.6_A refer to page 463
- EPIC® DATA AX RJ45 Cat.6_A IP68 refer to page 463
- EPIC® DATA RJ45F Cat.6_A refer to page 462
- EPIC® DATA M12X refer to page 465
- EPIC® DATA CCR FA refer to page 466
- DATA STRIP stripping tool refer to page 1001