



ETHERLINE® P Flex Cat.5e M12
Industrial Ethernet Patchcord M12



i Info

- Industrial Ethernet cable
- Other types are available on www.lappgroup.com/assemblyfinder or upon request

Benefits

- Non-permanent connections allow for easy change of equipment
- For directly connecting two electric components
- CAT.5-Performance

Application range

- Suitable for EtherCAT and EtherNet/IP applications
- Suitable for use in industrial applications
- For indoor use
- For flexible applications (7-wire stranded conductor)
- Automation technology

Product features

- Meets the requirements according to CAT.5e, ISO/IEC 11801 and EN 50173, Class D
- 2pair: 10/ 100 Mbit/s for Industrial Ethernet

Product Make-up

- Flexible fine-wire copper conductor
- Twisted pair construction permits largely interference-free operation (decoupling).
- Overall screening with copper braid and plastic-laminated aluminium foil
- Outer sheath made of PUR
- Colour: water blue (RAL 5021)
- Pre-assembled patchcords with M12 D-coded connectors
- 4 pole M12 connector with vibration protection

Technical data

- ETIM** ETIM 5.0 Class-ID: EC002599
ETIM 5.0 Class-Description: Patch cord copper (twisted pair) industry
- Minimum bending radius**
Flexing: 15 x outer diameter
Fixed installation: 8 x outer diameter
- Protection rating**
IP 67 / IP 69
- Characteristic impedance**
100 Ohm +/- 15%
- Temperature range**
Flexing: -5°C to +50°C (UL: +80°C)
Fixed installation: -30°C to +80°C

Article number	Article designation	Number of pairs and AWG per conductor	Length (m)	Copper index (kg/1.000 pieces)
straight plug M12 on straight plug M12				
2171097	IE-5-M12D-S-1-P-2-26-7-M12D-S	2x2xAWG26	1	19
2171098	IE-5-M12D-S-2-P-2-26-7-M12D-S	2x2xAWG26	2	38
2171099	IE-5-M12D-S-3-P-2-26-7-M12D-S	2x2xAWG26	3	57
2171100	IE-5-M12D-S-5-P-2-26-7-M12D-S	2x2xAWG26	5	95
2171101	IE-5-M12D-S-10-P-2-26-7-M12D-S	2x2xAWG26	10	190
2171102	IE-5-M12D-S-20-P-2-26-7-M12D-S	2x2xAWG26	20	380
straight plug M12 on free conductor end				
2171103	IE-5-M12D-S-1-P-2-26-7-OE	2x2xAWG26	1	19
2171104	IE-5-M12D-S-2-P-2-26-7-OE	2x2xAWG26	2	38
2171105	IE-5-M12D-S-3-P-2-26-7-OE	2x2xAWG26	3	57
2171106	IE-5-M12D-S-5-P-2-26-7-OE	2x2xAWG26	5	95
2171107	IE-5-M12D-S-10-P-2-26-7-OE	2x2xAWG26	10	190
2171108	IE-5-M12D-S-20-P-2-26-7-OE	2x2xAWG26	20	380

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
Copper price basis: EUR 150/ 100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
Other lengths and types of connectors are available upon request.
Photographs are not to scale and do not represent detailed images of the respective products.