



EPIC® H-B 10 TBFH

Housing design H-B. The industry standard.



Info

- More interior space for wiring
- Double lever version with 2 levers for increased safety

Benefits

- The smallest housing with single and double lever. The right housing is available for every application

Application range

- Plant engineering
- Light & sound technology
- Plastics industry

Product features

- Cable coupler hood, high version
- Dual levers
- Straight cable entry
- Versions with / without neck

Suitable inserts

- Refer to Selection Table A 10 to select the required inserts and housings

Technical data



ETIM 5.0 Class-ID: EC000437
ETIM 5.0 Class-Description:
Housing for industrial connectors



Material

Housing: powder-coated aluminium alloy, grey
Lever: zinc-plated steel
Sealing: NBR



Protection rating

IP 65 (latched)



Certified production control:
VDE-REG. no.: B437
UL-tested:
UL File Number: E75770



Temperature range

-40°C to +100°C,
short-term up to +125°C

Article number	Article description	M	PG	Neck	Pieces / PU
H-B housing: cable coupler hood (straight cable entry, double lever, high version)					
70040400	H-B 10 TBFH 21		21	yes	10
70040600	H-B 10 TBFH 29		29	yes	10
79040400	H-B 10 TBFH M25	25			10
79040600	H-B 10 TBFH M32	32			10

Photographs are not to scale and do not represent detailed images of the respective products.

Accessories

- SKINTOP® MS-M
- SKINTOP® for industrial connectors
- Easy to install