

Technical_data_MN_151

Version: 08/01/2023

Page 1/1

Technical data MN 151

acc. IEC 60947-3, EN 60947-3			
Rated operational current I_e	AC 21 A	A	32
Rated operational voltage U_e		V	690
Rated uninterrupted current I_{th}	open	A	32
Rated uninterrupted current I_{the}	encapsulated	A	32
Rated insulation voltage U_i Insulation group C acc. VDE 0110		V	690
Rated impulse withstand voltage U_{imp} (III/3)		kV	4
Making/braking capacity	Utilisation category		
	AC 3		
	230 V 3~	kW	5,5
	400 V 3~	kW	7,5
	690 V 3~	kW	11
Single-phase motor	230 V	kW	3
	400 V	kW	4
Making/braking capacity	Utilisation category		
	AC 23A(B)		
	230 V 3~	kW	7,5
	400 V 3~	kW	11
	690 V 3~	kW	15
Short-circuit capacity			
Max. fuse rating (gG-Char.)		A	35
Rated conditional short-circuit current		kA _{eff}	4
Rated short-time withstand current I_{cw1sec}		A	300
Rated short circuit making capacity I_{cm}		A	-
Isolating characteristics up to		V~	690
Terminal cross section solid or multi-stranded	min./max.	mm ²	1,0 - 6,0
Finely stranded with ferrule	min./max.	mm ²	1,0 - 2,5
Terminal screws			M3,5
Torque terminal screws		Nm	1
Mechanical life	Operating cycles		1x10 ⁶
Ambient temperature	open	°C	+50/-25
	encapsulated	°C	+40/-25
acc. UL und CSA 			
Rated operational current		A	20
Rated operational voltage		V	600
Making/braking capacity	Utilisation category		
	AC 3		
Motor 3-phase	220/240 V 3~	hp	5
	440/480 V 3~	hp	10
	550/600 V 3~	hp	10
Making/braking capacity	Utilisation category		
	AC 23A(B)		
Motor 1-phase	110/120 V	hp	1
	220/240 V	hp	3
Cable cross section		AWG-No	16 - 10

Subject to change without notice, errors and errata excepted.