




SKINTOP® MS-M-XL / SKINTOP® MSR-M-XL



Benefits

SKINTOP® MS-M-XL

- Especially for thick walls
- Maximum reliability
- Optimum strain relief
- Wide, variable clamping ranges

Application range

SKINTOP® MS-M-XL

- With long connection thread for applications involving a thicker wall.

SKINTOP® MSR-M-XL

- With reducing seal insert, to seal cables with smaller outer diameters.

Norm references / Approvals

- UL File Nr. E79903

Product Make-up

- Metric connection thread acc. to DIN EN 60423
- Basis for technical information DIN IEC 62444

Note

- Counter nut to be used: SKINDICHT® SM-M
- Refer to SKINTOP® metric accessories for suitable accessories

Technical data

- Classification ETIM 5/6**
ETIM 5.0/6.0 Class-ID: EC000441
ETIM 5.0/6.0 Class-Description: Cable screw gland
- Caution**
Refer to Appendix T21 for the installation dimensions and torques
- Material**
Body: nickel-plated brass
Insert: polyamide
Sealing: CR
O-ring: NBR
- Protection rating**
IP 68 - 10 bar
IP 69
NEMA Type 1, 4x, 6, 12
- Temperature range**
dynamic -25°C up to + 100°C
Fixed: -40°C to +100°C

Article number	Article designation / size	Clamping range ØF (mm)	SW wrench size mm	Overall length, C (mm)	Thread length, D (mm)	Pieces / PU
SKINTOP® MS-M-XL						
53112005	M 12 x 1,5	3-7	16	32.8	12	100
53112015	M 16 x 1,5	4,5-10	20	37.0	12	50
53112025	M 20 x 1,5	7-13	24	39.5	12	50
53112035	M 25 x 1,5	9-17	29	41.5	12	25
53112045	M 32 x 1,5	11-21	36	48.2	15	25
53112055	M 40 x 1,5	19-28	45	53.5	15	10
53112065	M 50 x 1,5	27-35	54	57.0	15	5
SKINTOP® MSR-M-XL						
53112105	M 12 x 1,5	1-5	16	32.8	12	100
53112115	M 16 x 1,5	2-7	20	37.0	12	50
53112125	M 20 x 1,5	5-10	24	39.5	12	50
53112135	M 25 x 1,5	6-13	29	41.5	12	25
53112145	M 32 x 1,5	7-15	36	48.2	15	25
53112155	M 40 x 1,5	15-23	45	53.5	15	10
53112165	M 50 x 1,5	22-29	54	57.0	15	5

Photographs and graphics are not to scale and do not represent detailed images of the respective products.