



ETHERLINE® ACCESS U05T/U08T

Unmanaged switches for industrial communication

i Info

- Redundant power inputs
- Robust metal housing and DIN rail mounting
- Fanless maintenance free



- Benefits**
- Improve your total cost of ownership with faster installation and lower downtime
 - Most flexible and globally present solutions from one hand

- Norm references / Approvals**
- Shock IEC 60068-2-27
 - Freefall IEC60068-2-32
 - Vibration IEC 60068-2-6

Technical data

- Classification ETIM 5/6**
ETIM 5.0/6.0 Class-ID: EC000734
ETIM 5.0/6.0 Class-Description: Network switch
- Protection rating**
IP 30
- Temperature range**
-10°C to +60°C

- Product features**
- RJ45 Ports: 10/100BaseT(X)
 - Packet Buffer Size: 512 kbit
 - Broadcast storm protection
 - Redundant Power Input: 24 VDC

Article number	Article designation	Type	RJ45 ports	MTBF in years
ETHERLINE® ACCESS U05T/U08T				
21700118	ETHERLINE® ACCESS U05T	Unmanaged	5	> 347
21700119	ETHERLINE® ACCESS U08T	Unmanaged	8	> 277

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

- Accessories**
- ETHERLINE® EC FD Cat.5e RJ4